

R-656

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF A PORTION OF THE
OREGON AND WASHINGTON STATE BOUNDARY,
AND
PORTIONS OF THE SOUTH, EAST, AND WEST BOUNDARIES
AND SUBDIVISIONAL LINES,
THE SUBDIVISION OF SECTIONS 14, 15, 20, 21, 22, AND 26,
AND METES-AND-BOUNDS SURVEY OF THE
THREAD OF HENRY CREEK IN SECTIONS 19, 20, 29, AND 30,
TOWNSHIP 6 NORTH, RANGE 38 EAST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

Richard L. Johnson, Cadastral Surveyor

Philip G. Griffin, Cadastral Surveyor

Larry D. Holmes, Cadastral Surveyor

Richard R. Shatto, Cadastral Surveyor

Under Special Instructions dated September 18, 1987,
approved September 18, 1987,
and Supplemental Special Instructions dated May 9, 1990,
approved May 11, 1990,
which provided for the surveys included under Group No. 1405,
and Assignment Instructions dated September 21, 1987,
May 19, 1988, May 16, 1990, and August 29, 1990.

Survey commenced October 13, 1987

Survey completed September 16, 1991

INDEX DIAGRAM

Township 6 North, Range 38 East,

WASHINGTON					
2		4		6	
27 18	17	16 46	15 41	14 34	13
	57	49	45	39	33
OREGON					
25 19 55	20 48	21 43	22 38	23 32	24
54		42	42	37	31
23 30 52	29	28	27 36	26 30	25
		35		35	30
21		42			
31 50	32	33	34 35	35 28	36 19
	18	15	12	10	7

Subdivision of Section 14	Pages 58-62
Subdivision of Section 15	Pages 62-65
Subdivision of Section 20	Pages 65-66
Subdivision of Section 21	Pages 66-67
Subdivision of Section 22	Pages 67-69
Subdivision of Section 26	Pages 69-71
Survey of Thread of Henry Creek in Secs. 19, 20, 29 and 30	Pages 71-73

T. 6 N., R. 38 E., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the Oregon and Washington State boundary, and portions of the south, east, and west boundaries and subdivisional lines, the subdivision of sections 14, 15, 20, 21, 22, and 26, and the metes-and-bounds survey of the thread of Henry Creek in sections 19, 20, 29, and 30, township 6 north, range 38 east, Willamette Meridian, Oregon.

In 1864, Daniel G. Major, Astronomer and Surveyor, surveyed the Oregon and Washington State boundary.

In 1865, William H. Odell and William S. Lewis, U. S. Deputy Surveyors, surveyed a portion of the west boundary.

In 1872, George Williams, U. S. Deputy Surveyor, retraced portions of the Oregon and Washington State boundary, and surveyed the south, east, and the remainder of the west boundary and subdivisional lines, T. 6 N., R. 38 E., south of the State boundary. Williams' retracement of the Oregon and Washington state boundary is irreconcilable with the original survey and is not utilized in this resurvey.

In 1879, Francis F. Loehr, U. S. Deputy Surveyor, retraced portions of the Oregon and Washington State boundary and surveyed the east boundary and subdivisional lines of T. 6 N., R. 38 E., north of the State boundary.

In 1883, Rufus S. Moore, U. S. Deputy Surveyor, retraced a portion of the south boundary.

In 1899, William and George R. Campbell, U. S. Deputy Surveyors, retraced a portion of the south boundary.

In 1931, Roy T. Campbell, U. S. Cadastral Engineer, retraced a portion of the Oregon and Washington State boundary.

In 1932, Otis O. Gould, U. S. Transitman, dependently resurveyed a portion of the State boundary, west boundary, and independently resurveyed the south boundary of T. 6 N., R. 39 E.

In 1965, C. Albert White, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines of T. 6 N., R. 37 E.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated September 18, 1987, and Supplemental Special Instructions dated May 9, 1990, for Group No. 1405, Oregon.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented by a variety of means based on the official record. Almost complete absence of original evidence throughout the township, the discovery of major blunders of measurement in the original survey of both the Oregon and Washington State boundary and the south boundary of the township, and the need to preserve

T. 6 N., R. 38 E., Willamette Meridian, Oregon

CHAINS

the bona fide rights of property owners dictated the use of eclectic methods. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation.

Detectable Electronically Energized Particles (DEEP-1 TM) were buried as memorials at certain corner monuments. The DEEP-1 is composed of strontium encased in a color coded plastic container. The units are 1 inch in diameter, 2½ inches long, weigh 2½ ounces, and are magnetically detectable to an average depth of 8 feet.

The geographic position (NAD 1927) of the ¼ section corner of sections 25 and 30 on the west boundary of the township, as determined by a direct tie to United States Geological Survey triangulation station "PIKES PEAK," 1960, is as follows:

Latitude 45° 58' 13.63" N. Longitude 118° 07' 19.60" W.

The mean magnetic declination is 21° East.

**Dependent Resurvey of a Portion of the
Oregon and Washington State Boundary,
T. 6 N., R. 38 E., Willamette Meridian, Oregon**

(Restoring the 1864 survey by Daniel G. Major
and the 1931 resurvey by Roy T. Campbell)

Beginning at the 40 Mile Post, determined from the remaining original bearing tree:

A ponderosa pine, 38 ins. diam., bears N. 86° E., 200 lks. dist., with scribe marks 40M on opened blaze facing W., and illegible scribe marks on opened blaze facing S.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

40 M
WASHINGTON
OREGON
1991

from which a new bearing tree

A ponderosa pine, 17 ins. diam., bears S. 3¼° W., 91½ lks. dist., mkd. 40M ORE BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

**Dependent Resurvey of a Portion of the East Boundary,
T. 6 N., R. 38 E., Willamette Meridian, Oregon**

CHAINS

From this point, the closing cor. of secs. 30 and 31, T. 6 N., R. 39 E., bears N. 5° 41' 00" W., 0.290 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, protruding 8 ins. above the ground, with brass cap mkd.

T 6 N		T 6 N
R 38 E		S 30
S 25		-----
		S 31
		R 39 E
C		C
1932		

from which the remains of bearing trees mkd. by Gould

A fir, 16 ins. diam., bears N. 65½° E., 56 lks. dist., with healed blaze. (Record, N. 67° E., 55 lks.)

A shattered fir stump, size indeterminate, bears S. 65½° E., 38½ lks. dist., with scribe marks BT on rotted and broken face. (Record, 37 lks.)

and a new bearing tree

A fir, 17 ins. diam., bears S. 44½° E., 76½ lks. dist., mkd. T6N R39E S31 CC BT.

The corner is located on NE. slope, 115 lks. S. of ravine, drains N. 20° W. and 45 lks. E. of ravine, drains N. 40° W.

**Dependent Resurvey of a Portion of the West Boundary,
T. 6 N., R. 38 E., Willamette Meridian, Oregon**

(Restoring the 1865 survey by William H. Odell and
William S. Lewis, and the 1872 survey by George Williams)

From the ¼ sec. cor. of secs. 31 and 36, perpetuated by Wayne O. Harris, Registered Land Surveyor No. 346, in 1960, recorded in the Umatilla County Surveyor's Office; monumented with the original corner tree, a yew, 6 ins. diam., no marks, from which the remains of the original bearing trees:

A fir snag, 40 ins. diam., bears S. 60° E., 12 lks. dist., mkd. with axe marks on opened blaze. (Record, S. 47° E.).

A root hole, bears S. 38° W., 25 lks. dist.

and a reference monument by Harris

An iron pipe, 2 ins. diam., firmly set, protruding 12 ins. above the ground, bears S. 60¾° E., 1 lk. dist.

and a new bearing tree and reference monument

Dependent Resurvey of a Portion of the West Boundary,
T. 6 N., R. 38 E., Willamette Meridian, Oregon

CHAINS													
	<p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° E., 10 lks. dist., with brass cap mkd. RM ¼ S31 T6N R38E 6.6 FT TO COR 1991 and an arrow pointing to the corner. Deposit a silver "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>A yew, 11 ins. diam., bears S. 8½° W., 37½ lks. dist., mkd. ¼ S36 BT.</p> <p>The corner is located on level ground, 40 lks. E. of a dirt road, 20 lks. wide, bears N. 30° W. and S. 30° E.</p> <p>N. 0° 01' 00" W., bet. secs. 31 and 36.</p> <p>Over level ground through timber and undergrowth.</p>												
0.50	Dirt road, 20 lks. wide, bears N. 50° W. and S. 50° E.												
13.60	Ravine, drains N. 20° E.												
20.60	Dirt road, 30 lks. wide, bears N. 45° W. and S. 45° E.												
39.040	<p>Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T6N</td></tr> <tr><td>R37E</td><td>R38E</td></tr> <tr><td>S 25</td><td>S 30</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 36</td><td>S 31</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>from which</p> <p>A fir, 10 ins. diam., bears N. 61° E., 74 lks. dist., mkd. T6N R38E S30 BT.</p> <p>A fir, 11 ins. diam., bears S. 68° E., 85½ lks. dist., mkd. T6N R38E S31 BT.</p> <p>A fir, 9 ins. diam., bears S. 84½° W., 54½ lks. dist., mkd. T6N R37E S36 BT.</p> <p>A fir, 7 ins. diam., bears N. 21¼° W., 57½ lks. dist., mkd. T6N R37E S25 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located on gentle S. slope in timber and undergrowth.</p>	T6N		R37E	R38E	S 25	S 30			S 36	S 31	1991	
T6N													
R37E	R38E												
S 25	S 30												
S 36	S 31												
1991													

Dependent Resurvey of a Portion of the West Boundary,
T. 6 N., R. 38 E., Willamette Meridian, Oregon

CHAINS

From this point, a point reestablished as the cor. of secs. 25, 30, 31 and 36, recorded by Wayne O. Harris, Registered Land Surveyor No. 346, in 1961, in the Umatilla County Surveyor's Office, bears S. 43° 33' 00" W., 1.705 chs. dist., monumented with an iron rod, 1 in. square, firmly set flush with the ground. This point is not properly positioned and is not utilized in this survey, from which the remains of bearing trees mkd. by Harris:

A root hole, bears N. 84° E., 20½ lks. dist., with fir stump lying alongside, no marks

A larch, 18 ins. diam., bears S. 18° W., 62 lks. dist., with healed blaze.

From the same point, a point established as the approximate cor. of secs. 25, 30, 31, and 36 by Howard E. Taylor, Registered Engineer No. 2891, in 1956, not monumented, determined from a bearing tree mkd. by Taylor, bears N. 11° 58' 00" W., 1.195 chs. dist. This point is not properly positioned and is not utilized in this survey, from which a bearing tree mkd. by Taylor:

A fir, 21 ins. diam., bears S. 5° E., 10 lks. dist., with metal tag mkd. APPROX NW COR, THIS COR IS 2660 FT NORTH OF GOOD W¼ S31 I FIND NO ORIG BT'S, 6/25/56.

N. 0° 01' 00" W., bet. secs. 25 and 30.

Ascend gentle SE. slope through timber and undergrowth.

1.25 Down barbed wire fence, 3 strands, extending E. and W.

9.50 Leave timber, edge bears N. 70° W. and S. 70° E.; enter grassy ground.

39.040 Point for the ¼ sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T6N
¼
R37E R38E
S 25 | S 30
1991

from which

A fir, 27 ins. diam., bears S. 20¾° E., 406½ lks. dist., mkd. ¼ S30 BT.

A fir, 9 ins. diam., bears S. 27° W., 154 lks. dist., mkd. ¼ S25 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

Dependent Resurvey of a Portion of the West Boundary,
T. 6 N., R. 38 E., Willamette Meridian, Oregon

CHAINS

The corner is located on grassy ground on very steep E. slope, 235 lks. E. of top of ascent, edge bears N. and S.

From this point, a point reestablished as the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, recorded by Wayne O. Harris, Registered Land Surveyor No. 346, in 1960, in Umatilla County Surveyor's Office, bears N. $79^{\circ} 56' 30''$ W., 2.125 chs. dist., monumented with an iron rod, 1 in. diam., firmly set, projecting 4 ins. above ground. This point is not properly positioned and is not utilized in this survey, from which the remains of a bearing tree mkd. by Harris:

A ponderosa pine snag, 29 ins. diam., bears N. 78° W., 72 lks. dist., with scribe marks 6N R37 $\frac{1}{4}$ S S25 on partially healed blaze.

From the same point, United States Geological Survey triangulation station "PIKES PEAK," bears S. $33^{\circ} 36' 00''$ W., 3.020 chs, dist., monumented with a brass tablet, 4 ins. diam., firmly set into rock ledge, mkd. USGS PIKES PEAK 1960 and a triangle.

42.65

Rocky spur, slopes N. 75° E.; desc. broken NE. slope.

78.080

Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T6N	
R37E	R38E
S 24	S 19

S 25	S 30
1991	

from which

A ponderosa pine, 19 ins. diam., bears N. $70\frac{1}{2}^{\circ}$ E., 185 $\frac{1}{2}$ lks. dist., mkd. T6N R38E S19 BT.

A fir, 22 ins. diam., bears S. 59° E., 88 lks. dist., mkd. T6N R38E S30 BT.

A fir, 24 ins. diam., bears S. $23\frac{1}{4}^{\circ}$ W., 14 lks. dist., mkd. T6N R37E S25 BT.

A fir, 26 ins. diam., bears N. $74\frac{1}{4}^{\circ}$ W., 29 lks. dist., mkd. T6N R37E S24 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

The corner is located in timber and undergrowth.

From this point, a point reestablished as the cor. of secs. 19, 24, 25 and 30, recorded by Wayne O. Harris, Registered Land Surveyor No. 346, in 1960, in the Umatilla County Surveyor's Office, bears N. $69^{\circ} 51' 00''$ W., 1.630 chs. dist., monumented with

Dependent Resurvey of a Portion of the West Boundary,
T. 6 N., R. 38 E., Willamette Meridian, Oregon

CHAINS	
	<p>an iron rod, 1 in. square, firmly set 18 ins. below ground. This point is not properly positioned and is not utilized in this survey, from which the remains of bearing trees mkd. by Harris:</p> <p>A fir stump, 26 ins. diam., bears S. $83\frac{1}{2}^{\circ}$ E., 39 lks. dist., no marks.</p> <p>A fir stump, 31 ins. diam., bears S. $73\frac{3}{4}^{\circ}$ W., $12\frac{1}{2}$ lks. dist., with illegible scribe marks on partially healed blaze.</p> <p>A fir, 32 ins. diam., bears N. $49\frac{3}{4}^{\circ}$ W., 19 lks. dist., no marks on partially healed blaze.</p>
39.040	<p>N. $0^{\circ} 01' 00''$ W., bet. secs. 19 and 24.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T6N $\frac{1}{4}$ R37E R38E S 24 S 19 1991</p>
	<p>from which</p> <p>A fir, 12 ins. diam., bears N. $14\frac{1}{4}^{\circ}$ E., $24\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S19 BT.</p>
	<p>A larch, 23 ins. diam., bears N. $20\frac{1}{2}^{\circ}$ W., $14\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S24 BT.</p>
	<p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p>
	<p>The corner is located on E. slope, 310 lks. E. of a spur, with jeep trail, 15 lks. wide, bears N. and S.</p>
	<p>From this point, a point reestablished as the $\frac{1}{4}$ sec. cor. of secs. 19 and 24, recorded by Wayne O. Harris, Registered Land Surveyor No. 346, in 1960, in the Umatilla County Surveyor's Office, bears N. $60^{\circ} 13' 00''$ W., 1.115 chs. dist., monumented with an iron rod, 1 in. square, firmly set, protruding 1 in. above the ground. This point is not properly positioned and is not utilized in this survey, from which a bearing tree mkd. by Harris:</p>
	<p>A fir, 31 ins. diam., bears S. $2\frac{1}{4}^{\circ}$ E., 29 lks. dist., with healed double blaze.</p>
73.50	<p>Creek, 5 lks. wide, course N. 60° E.</p>
74.65	<p>Dirt road, 15 lks. wide, bears N. 70° E. and S. 70° W.</p>
75.10	<p>Dry creek, 5 lks. wide, drains N. 65° E.; asc. SE. slope.</p>

**Dependent Resurvey of a Portion of the West Boundary,
T. 6 N., R. 38 E., Willamette Meridian, Oregon**

CHAINS

78.080

Point for the cor. of secs. 13, 18, 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in collar of stone, with brass cap mkd.

	T6N	
	R37E	R38E
S 13		S 18

S 24		S 19
1991		

from which

A fir, 22 ins. diam., bears N. 20½° E., 70 lks. dist., mkd.
T6N R38E S18 BT.

A fir, 6 ins. diam., bears S. 48° E., 102½ lks. dist., mkd.
T6N R38E S19 BT.

A fir, 16 ins. diam., bears S. 74½° W., 57 lks. dist., mkd.
T6N R37E S24 BT.

A fir, 21 ins. diam., bears N. 12° W., 106½ lks. dist., mkd.
T6N R37E S13 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

The corner is located on SE. slope in scattered timber and light undergrowth, 20 lks. E. of a dirt road, 20 lks. wide, bears N. 10° E. and S. 20° W.

From this point, a point reestablished as the cor. of secs. 13, 18, 19 and 24, recorded by Wayne O. Harris, Registered Land Surveyor No. 346, in 1960, in the Umatilla County Surveyor's Office, bears N. 36° 56' 30" W., 0.655 chs. dist., monumented with an iron rod, 1 in. square, firmly set flush with ground. This point is not properly positioned and is not utilized in this survey. This corner was tied to and utilized for control by C. Albert White, Cadastral Surveyor, during a dependent resurvey in T. 6 N., R. 37 E., in 1965; from which a bearing tree mkd. by Harris:

A ponderosa pine, 21 ins. diam., bears N. 78½° E., 42 lks. dist., with scribe marks T6 R38 S1 S BT on partially healed blaze.

From the same point, the cor. of secs. 13, 14, 23 and 24, T. 6 N., R. 37 E., reestablished by C. Albert White, Cadastral Surveyor, in 1965, bears N. 88° 14' 30" W., 78.640 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, protruding 8 ins. above the ground, with brass cap mkd.

	T6N	R37E
S 14		S 13

S 23		S 24
1965		

Dependent Resurvey of a Portion of the West Boundary,
T. 6 N., R. 38 E., Willamette Meridian, Oregon

CHAINS							
	<p>from which bearing trees mkd. by White</p> <p>A fir, 19 ins. diam., bears N. $82\frac{1}{2}^{\circ}$ E., 87 lks. dist., with healed blaze.</p> <p>A fir, 24 ins. diam., bears S. 63° E., 29 lks. dist., with healed blaze.</p> <p>A fir, 18 ins. diam., bears S. $15\frac{1}{2}^{\circ}$ W., 43 lks. dist., with healed blaze.</p> <p>A fir, 17 ins. diam., bears N. $48\frac{1}{2}^{\circ}$ W., 132 lks. dist., with healed blaze.</p>						
	<hr/> <p>N. $0^{\circ} 01' 00''$ W., bet. secs. 13 and 18.</p> <p>Ascend gentle SE. slope through timber and undergrowth.</p>						
0.90	Dirt road, 20 lks. wide, bears N. 10° E. and S. 20 W.						
3.65	Spur, slopes E.; desc. steep N. slope.						
5.30	Creek, dry, 10 lks. wide, drains N. 50° E.; asc. SE. slope.						
37.35	Spur, slopes E.; desc. steep N. slope.						
38.20	Jeep track, 15 lks. wide, bears N. 70° W. and S. 70° E.						
39.040	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6N</p> <p>$\frac{1}{4}$</p> <table style="margin: auto;"> <tr> <td>R37E</td> <td>R38E</td> </tr> <tr> <td>S 13</td> <td>S 18</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>from which</p> <p>A fir, 29 ins. diam., bears N. 58° E., 52 lks. dist., mkd. $\frac{1}{4}$ S18 BT.</p> <p>A fir, 15 ins. diam., bears S. $49\frac{3}{4}^{\circ}$ W., 36 lks. dist., mkd. $\frac{1}{4}$ S13 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located on steep NE. slope.</p> <p>From this point, a point reestablished as the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, recorded by Wayne O. Harris, Registered Land Surveyor No. 346, in 1960, in Umatilla County Surveyor's Office, bears N. $16^{\circ} 51' 30''$ E., 0.450 chs. dist., monumented with an iron rod,</p>	R37E	R38E	S 13	S 18	1991	
R37E	R38E						
S 13	S 18						
1991							

**Dependent Resurvey of a Portion of the West Boundary,
T. 6 N., R. 38 E., Willamette Meridian, Oregon**

CHAINS

1 in. square, firmly set, protruding 4 ins. above the ground. This point is not properly positioned and is not utilized in this survey, from which a bearing tree mkd. by Harris:

A fir, 19 ins. diam., bears S. 82° E., 41½ lks. dist., with healed blaze.

41.45 Creek, dry, 20 lks. wide, drains S. 75° E., over level ground.

41.65 Dirt road, 15 lks. wide, bears N. 75° W. and S. 75° E.; asc. steep rocky S. slope.

50.360 Intersect the Oregon and Washington State bdy. and true point for the closing cor. of secs. 13 and 18.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T6N	R37E
S 13	S 18
S 13	S 18
R37E	R38E
C	C
T6N	
1991	

from which

A ponderosa pine, 20 ins. diam., bears S. 54½° E., 114 lks. dist., mkd. T6N R38E S18 CC BT.

A fir, 16 ins. diam., bears S. 63° W., 260 lks. dist., mkd. T6N R37E S13 CC BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, a point reestablished as the closing cor. of secs. 13 and 18, recorded by Wayne O. Harris, Registered Land Surveyor No. 346, in 1960, in Umatilla County Surveyor's Office, bears N. 0° 01' 00" W., 0.450 chs. dist. There is no remaining evidence of the original corner; therefore, this position is accepted as the corner, monumented with an iron rod, 1 in. square, firmly set, protruding 6 ins. above the ground, from which a bearing tree mkd. by Harris:

A fir, 22 ins. diam., bears S. 33½° E., 193 lks. dist., with healed double blaze.

From this same point, the 41st Mile Post on the Oregon and Washington State bdy., bears N. 89° 57' 30" E., 15.270 chs. dist., hereinbefore described.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 N., R. 38 E., Willamette Meridian, Oregon**

**Survey of the Thread of Henry Creek in Sections 19, 20, 29 and 30,
T. 6 N., R. 38 E., Willamette Meridian, Oregon**

CHAINS	
N. 18° 41' 30" E., 2.695 chs.	
N. 40° 33' 30" E., 1.685 chs.	At 0.605 chs. intersect the line bet. secs. 19 and 20, 6.115 chs. N. 6° 20' 00" E. of the cor. of secs. 19, 20, 29, and 30; thence in sec. 20.
N. 2° 20' 00" E., 2.300 chs.	
N. 55° 54' 30" E., 2.765 chs.	
N. 29° 53' 30" E., 2.250 chs.	
N. 10° 55' 00" W., 1.510 chs.	
N. 49° 56' 00" E., 3.835 chs.	
N. 7° 17' 30" E., 2.240 chs.	
N. 49° 57' 30" E., 1.560 chs.	
N. 74° 45' 00" E., 2.730 chs.	
N. 33° 06' 00" E., 1.730 chs.	
N. 45° 14' 00" E., 6.640 chs.	
N. 53° 17' 30" E., 1.390 chs.	
N. 18° 16' 00" E., 1.540 chs.	
N. 51° 23' 30" E., 1.815 chs.	
N. 9° 14' 30" E., 1.670 chs.	
N. 43° 47' 00" E., 3.210 chs.	
N. 52° 04' 30" E., 2.455 chs.	
N. 25° 11' 30" E., 3.235 chs.	
N. 47° 13' 30" E., 0.920 chs.	At end of course, intersect the E. and W. center line of sec. 20, 22.460 chs. N. 89° 54' 00" E. of the ¼ sec. cor. of secs. 19 and 20.
GENERAL DESCRIPTION	
<p>The lands included in this survey are located approximately 15 miles southeast of Walla Walla, Washington, in Umatilla County, Oregon. Elevation ranges from 2200 feet to 5500 feet above sea level. The township is cut in half by Mill Creek with many smaller creeks draining into it. The land consists of steep ridges and spurs sloping into Mill Creek. That area east of Tiger Ridge contains the city of Walla Walla, Washington watershed.</p>	

T. 6 N., R. 38 E., Willamette Meridian, Oregon

CHAINS

The timber consists of fir, cedar, pine, yew, larch and alder. The timber is found mainly in the draws and on north slopes. In the wetter areas the undergrowth consists of young timber, salmonberry, vine maple, devils club, and Russian thistle. On the dry south and southeast slopes the undergrowth is grasses and star thistle.

The State boundary and that part of the township north of Mill Creek is accessed by Blue Creek Road. That part south of Mill Creek is accessed by Mill Creek Road, with graveled and dirt roads extending southerly into the township. The east one-half is accessed by Tiger Creek Road. The south boundary of the township is accessed from Government Road, off from Tiger Creek Road.

Improvements are mostly contained along Mill and Henry Creeks, consisting of homes and homesteads. A dam, water supply intake, and caretakers building for the water supply of Walla Walla, Washington, are located on Mill Creek in the northwest quarter of section 22.

The principal money making enterprises are the harvest of timber and the grazing of cattle. No evidence of any mining activity was observed in the area.

The mean magnetic declination for the area is 21° East, with a range of 3° in local attraction, as determined from a considerable number of readings taken along the lines surveyed.

CERTIFICATE OF SURVEY

We, Richard L. Johnson, Philip G. Griffin, Larry D. Holmes, and Richard R. Shatto, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 18th day of September 1987, and supplemental special instructions bearing date of the 9th day of May 1990, we have dependently resurveyed a portion of the Oregon and Washington State Boundary, and a portion of the south, east, and west boundaries and subdivisional lines, subdivided sections 14, 15, 20, 21, 22, and 26, and surveyed the metes-and-bounds of the thread of Henry Creek in sections 19, 20, 29, and 30, township 6 north, range 38 east, of the Willamette Meridian, in the State of Oregon, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

3/31/93
Date

Richard L. Johnson
Cadastral Surveyor

4/08/93
Date

Larry D. Holmes
Cadastral Surveyor

4/08/93
Date

Richard R. Shatto
Cadastral Surveyor

May 5, 1993
Date

Philip G. Griffin
Cadastral Surveyor

CERTIFICATE OF APPROVAL

Bureau of Land Management
Portland, Oregon

The foregoing field notes of the dependent resurvey of a portion of the Oregon and Washington State Boundary, and a portion of the south, east, and west boundaries and subdivisional lines, the subdivision of sections 14, 15, 20, 21, 22, and 26, and the metes-and-bounds survey of the thread of Henry Creek in sections 19, 20, 29, and 30, township 6 north, range 38 east, Willamette Meridian, Oregon, executed by Richard L. Johnson, Philip G. Griffin, Larry D. Holmes, and Richard R. Shatto, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

June 25, 1993
Date

Wayne M. Gardner
Chief Cadastral Surveyor of Oregon

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in T. 6 N., R. 38 E., Willamette Meridian, Oregon, is a true copy of the original field notes.

Date

Chief Cadastral Surveyor of Oregon