

# FIELD NOTES

OF THE SURVEY OF THE

RESURVEY OF PART OF OREGON AND WASHINGTON BOUNDARY;

RESURVEY OF PART OF EAST BOUNDARY

OF

TOWNSHIP 6 NORTH, RANGE 39 EAST;

SURVEY OF PART OF EAST BOUNDARY

AND

SURVEY OF PART OF SUBDIVISION

OF

TOWNSHIP 6 NORTH, RANGE 40 EAST

Of the WILLAMETTE Meridian,

In the State of WASHINGTON

EXECUTED BY

ROY T. CAMPBELL, U. S. Cadastral Engineer

In the capacity of U. S. Surveyor..., under Special Instructions dated April 17, 1929, 1929, issued by the United States Surveyor General to govern surveys included in Group No. 130, which were approved by the Commissioner of the General Land Office, May 14, 1929, 1929, and Assignment Instructions dated June 1, 1931, 1931, 1931

E. D. C.

Survey commenced July 1, 1932, 1932

Survey completed August 7, 1932, 1932

Approved Oct. 11. 1934 Accepted Feb. 27, 1935

453

470

# FIELD NOTES

DATE

and

## INDEX DIAGRAM.

Township 6 North, Range 40 East

see p. 302

12	38	33	28	23	17	14
8-5-32 <sup>6</sup>	8-4-32 <sup>5</sup>	8-3-32 <sup>4</sup>	7-9-32 <sup>3</sup>	7-7-32 <sup>2</sup>	7-5-32 <sup>1</sup>	7-1-32
41	39	34	29	24	19	
8-5-32	8-5-32	7-11-32	7-9-32	7-7-32	7-5-32	
13	42	35	30	25	20	15
8-5-32 <sup>7</sup>	8-4-32 <sup>8</sup>	8-3-32 <sup>9</sup>	7-11-32 <sup>10</sup>	7-8-32 <sup>11</sup>	7-6-32 <sup>12</sup>	7-2-32
44	43	37	32	27	21	
8-6-32	8-6-32	7-12-32	7-12-32	7-8-32	7-6-32	17
8-5-32 <sup>10</sup>	8-4-32 <sup>9</sup>	8-3-32 <sup>7</sup>	7-11-32 <sup>5</sup>	7-8-32 <sup>4</sup>	7-6-32 <sup>2</sup>	7-2-32
8-7-32 <sup>15</sup>	8-7-32 <sup>17</sup>	8-1-32 <sup>16</sup>	7-12-32 <sup>15</sup>	7-8-32 <sup>14</sup>	7-6-32 <sup>13</sup>	
19	20	21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	

471

RESURVEY OF PART OF OREGON AND WASHINGTON BOUNDARY

Chains

Chains

W  
S 18  
514

Leave rocky opening; enter scattering timber and undergrowth, bears N. and descends 50 ft. over rugged W. slope.

1932

The  $\frac{1}{4}$  sec. cor. of sec. 17 only, T. 6 N., R. 40 E., from which above ground, firmly set, marked and witnessed as described in the record of the "Resurvey of Part of the Oregon and Washington Boundary", Group 135, Oregon.

A fir, 14 ins. diam., bears N. 9° E., 46 lks. dist., mkd. L 4 S 18 B T.

A larch, 16 ins. diam., bears N. 45° W., 90 lks. dist., mkd. L 5 S 18 B T.

Descend 125 ft. over northwesterly slope.

81.97 The  $\frac{1}{4}$  sec. cor. of sec. 18 only, T. 6 N., R. 40 E., Oregon, which is an iron post, 1 in. diam., 10 ins. above ground, firmly set, marked and witnessed as described in the record of the "Resurvey of Part of the Oregon and Washington Boundary", Group 135, Oregon.

Descend 50 ft. over northwesterly slope.

84.80 Creek, 5 lks. wide, course NE.; ascend 420 ft. over SE. slope.

94.77 The true point for closing cor. of Tps. 6 N., Rs. 39 and 40 E., South, 32 lks. dist. from the witness cor., which is an iron post, 3 ins. diam., 24 ins. above ground and in mound of stone, firmly set, marked and witnessed as described in the official record of the "Resurvey of Part of Oregon and Washington Boundary", T. 6 N., R. 39 E., this group.

Land, mountainous.  
Soil, sandy loam, stony; 3rd and 4th rate.  
Timber, fir, yellow pine, spruce, and larch; undergrowth, 2nd growth fir, pine, spruce, and larch, huckleberry, vine maple, salal, small alder, elder, small mountain mahogany, mountain laurel, mountain ash, Oregon grape, fern, rose, small yew, and willow.

-----  
The closing cor. of sec. 17 and 18, T. 6 N., R. 40 E., Oregon, which is an iron post, 3 ins. diam., 12 ins. above ground, firmly set, marked and witnessed as described in the record of the "Resurvey of Part of the Oregon and Washington Boundary", Group 135, Oregon.

Dependent resurvey of the survey as originally executed by Roy T. Campbell, U. S. Cadastral Engineer, in 1931.

Note: For topography along Part of E. bdy. of T. 6 N., R. 39 E., see official records of "Part of East Boundary of T. 6 N., R. 39 E.", this group.

From the cor. of Tps. 6 and 7 N., Rs. 39 and 40 E., which is an iron post, 3 ins. diam., 12 ins. above ground, firmly set, marked and witnessed as described in the official records of the "South Boundary of T. 7 N., R. 40 E.", this group,

South, bet. secs. 1 and 6.

40.00 The  $\frac{1}{4}$  sec. cor. established for sec. 1 only, which is an iron post, 1 in. diam., 9 ins. above ground, firmly set, marked and witnessed as described in the official record of "Part of East Boundary of T. 6 N., R. 39 E."

508

I, Roy T. Campbell, U.S. Cadastral Engineer, hereby certify upon honor that in pursuance of special instructions received from the District Cadastral Engineer for Washington

bearing date of the 17th day of August, 1929, I have well, faithfully, and truly

4-680  
(August, 1926)

in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instru-

tions, and the laws of the United States, portions of

FIELD ASSISTANTS.

Part of Township No. 4 North, Range No. 40 East

NAMES.	CAPACITY.
John C. Temple	Chairman
Rex R. Campbell	"
Robert G. Yates	"
Marion D. Husk	Axman
Ray O. Davis	"
Leonard Sundell	Cornerman
Keville E. Craft	Flagman
APPROVAL	

6-2764

examined by Roy T. Campbell, U.S. Cadastral Engineer, under his special instructions dated April 17, 1929, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

I certify that the foregoing transcript of the field notes of the above described surveys has been correctly copied from the original notes on file in this office.

U.S. Supervisor of Surveys

CERTIFICATE OF UNITED STATES SURVEYOR

508

I, Roy T. Campbell, U.S. Cadastral Engr, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Washington bearing date of the 17th day of April, 1929, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of

Part of Township No. 6 North, Range No. 40 East

of the Willamette

Meridian, in the State of Washington, which are represented in and preliminary data and on the dates shown the foregoing field notes/as having been executed by me, and under my direction;/and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Washington and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

Olympia, Washington, March 31, 1934

Roy T. Campbell U. S. Cadastral Engineer

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS,

Denver, Colorado, OCT 11 1934, 19

The foregoing field notes of the survey of Fractional Township No. 6 North, Range No. 40 East of the Willamette Meridian, Washington,

executed by Roy T. Campbell, U. S. Cadastral Engineer,

under his special instructions dated April 17, 1929, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above described surveys in

has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.