FIELD NOTES.

On the survey of the Esterior
Lines of T5S. R296, T6S, R32, 337346, T9S.
Rs.33 +34 E. T85. R 33 +34 Ex Tys. Rs.33 +34 EWillamette Meridian,
Oregon, as surveyed by Frank W Cumpbell
U. S. Deputy Surveyor, under his Contract No. 468
dated April 12" — 1883
Suryey commenced Ofinil 28" — 1883
Survey completed July 17" 1883
NAMES AND DUTIES OF ASSISTANTS.
, Compassman.
, Compassman. , Chainman.
, Chainman.
Chainman. John, S. Guttrielije, Chainman. Frank Elliz, Chainman.
John S. Guttrielge, Chainman.
, Chainman. John, S. Guttrielije, Chainman. Frank Elliz, Chainman.

PRELIMINARY OATHS OF ASSISTANTS. we, John S. Guttridge and Frank Ellis do solemnly swear that we will faithfully execute the duties of Chain Carriers, that we will level the chain over even and uneven ground, and plumb the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we will assist in measuring, to the best of our skill and ability, and in accordance with the instructions given us in the survey of the Outerior lines of T.50 R 296, T6S. R532,337346. T95, R5337346+ T85 Rs337348.775 Rs,33r34 &-Willamette Meridian, Oregon. Chainman. Chainman. Chainman. Chainman. Subscribed and sworn to before me, this __ , do solemnly swear that we will well and truly perform the duties of Axemen in the establishment of corners and other duties, according to instructions given us, and to the best of our skill and ability Ts. In the survey of the 6x1 Erior lines of T55. R29 &. T. 65. Rs 32. 33 + 34 & 8795 Rs 33 V 346. Willamette Meridian, Oregon. Axeman. Subscribed and sworn to before me, this__ [SEAL.]

Willamette Meridian, Oregon. rook 3 lks. mide como et basalt stone 16 x 15 x 8 min 10 ms. in ground for 1/4 -200 sec cor marked 14 on M. face; from which, Aprine 18 ms. dia. br. 0/. 12°6, 5 lks. dist. marked 1/4 & B. B.J. Apme 12 ms. dia. brs, D. 440 M. 42 lks. dist, marked /4 S. B.J. 65.25 Springbranch 2 lks. wide course of M. 67.75 " Antersect Standard line at 4.39 chains O. of corito secs. 35 and 36 - and set a pine post 4ft. long Hins, square 24 ins. in ground marked 6.6.5.0.326. 1 on S.M. T. 68. R. 33 E. S. C. , S. C., faces, with 6 notches on & O. y W. edge;

Willamette Meridian, Oregon. Land mountainous Soil 2 nd rate. Densely covered with forests of June, fir, spruce, tomarack & yew and alder timber, 74.00 chs. Thick under growth of small June, fir spruce, tomarack & boilon 14.00 chs. June 4th 1883 General Description This Township is cough broken and mountainous. covered with deuse Forcots of pine. sprnee. fir and tamarach. Soil. 1st. 2d. 3d + 4" vales

FINAL OATHS FOR SURVEYS.

A list of the names of the individuals employed by	
Frank W. Campbell,	S. Deputy Surveyor, to assist in
running, measuring and marking the lines and corners described in the foregoing fold	
notes of the survey of the & X terrior lines of	T55. R296
notes of the survey of the 6xterior lines of 7.68.728.32.330346. Hines of Ty. 8	798. RS337
346,	-Willamette Meridian, Oregon,
showing the respective capacities in which they acted:	- Williamette Meridian, Oregon,
	, Compassman.
dolor & Gitte	, Chainman.
- Jovo D. Suanago	, Chainman.
7	, Chainman.
Trans Plus	, Chainman.
	, Axeman.
Daney Il Matteress	, Axeman.
	, Flagman.
FINAL OATHS OF ASSI	STANTS.
Frank W. Campbell , U. S. De	
Frank W. Campbell , U. S. De	outy Surveyor, in surveying all
those parts or portions of the Exterior lines	of T55 R-2,96
768, Rs32, 337346	76 C 7 0 TO C
Rs 337346,	1-1-2-1-1-0-1-9-0-1
as are represented in the foregoing field notes as having t	Willamette Meridian, Oregon,
his direction; and that said survey has been, in all respectant belief, well and faithfully surveyed, and the corner me to the instructions furnished by the U.S. Surveyor General	ts, to the best of our knowledge
Sohn, Of Attoday	, Compassman.
The state of the s	, Chainman.
El-rant 10110	, Chainman.
	, Chainman.
	, Chainman.
Casas Whattooks	, Axeman.
	, Axeman.
	, Flagman.
Subscribed and sworn to before me, this _ twenty	1 Sitte day of
August-	
Ong 11 1 1 1 1 1 1	
[SEAL] July Wy Cleup Beef	
Wed WE puty Surveyor	

I, Frank It Campbell
United States Deputy Surveyor, do solemnly swear that in pursuance of
instructions received from Jumes & Folman
U. S. Surveyor General for Oregon, bearing date of the 12th
day of, 1883, I have well, faith-
fully and truly, in my own proper person, and in strict conformity with
the instructions furnished by the U.S. Surveyor General for Oregon, the
Surveying Manual, and the Laws of the United States, surveying all those
parts or portions of Exterior lines of T. 5 S. R 296, TGS
Rs32,33734 & T.ps. 7.8898 Rs. 337346.
Willamette Meridian, in the State of Oregon, as are represented in the foregoing Field Notes as having been surveyed by me and under my directions; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the Surveying Manual, Printed Instructions, the Special Written Instructions
of the U. S. Surveyor General for Oregon, and in the specific manner described in the Field Notes, and that the foregoing are the <i>true</i> Field Notes of such survey, and should any fraud be detected I will suffer the penalty of perjury under the provisions of an Act of Congress approved August
8th, 1846. Frankly Caren Leol
U. S. Deputy Surveyor.
Subscribed and sworn to before me, this

day of October 188

2.247

OFFICE U. S. SURVEYOR GENERAL,

Portland, Oregon, Jany 7, 1884
The following Field Notes of the Survey of the
Exteriors of the foregoing Town- ships, as
executed by Frank W. Campbell
under his Contract No.468, dated. Ofund
12 %— 1883, having been critically examined,
the necessary corrections and explanations made, the said
Field Notes and the survey they describe are hereby approved.
Domes & Tolman
Surveyor General.