

INDEX DIAGRAM

Township 6 South, Range 33 East,

6	5	4	3	2	1
	<u>8</u>	<u>7</u>	<u>5</u>		<u>5</u>
7	8	9	10	11	<u>4</u> 12
					<u>3</u>
18	17	16	15	14	13
		<u>6</u>			
19	20	21	22	23	24
30	29	28	27	26	25
	<u>7</u>				
31	32	<u>6</u> 33	34	35	36
<u>3</u>	<u>2</u>	<u>2</u>	<u>1</u>	<u>1</u>	

T. 6 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points, township 6 south, range 33 east, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, with New Accessories when Needed".

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

South Boundary, T. 6 S., R. 33 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by Frank W. Campbell,
U. S. Deputy Surveyor, in 1883)

The cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., determined at record bearing and distance from the remains of the original bearing trees:

A fir, 35 ins. diam., bears N. 81° E., 38 lks. dist., with fragmentary scribe marks visible on open blaze.

A larch, 45 ins. diam., bears S. 17° W., 80 lks. dist., with fragmentary scribe marks visible on open blaze.

A pine, 46 ins. diam., bears N. 10° W., 62 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 33 E
S 33 S 34
S 4 S 3
T 7 S
1977

from which a new bearing tree

A larch, 11 ins. diam., bears S. 52° E., 28 lks. dist., mkd. T7S R33E S3 BT.

Corner is located 70 lks. north of gravelled road, 20 lks. wide, bears E. and W.

The ¼ sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp., monumented with the original unmarked granite stone, 18 x 13 x 4 ins., (record, 18 x 13 x 11 ins) firmly set 8 ins. in the ground, from which the remains of the original bearing trees:

A pine, 34 ins. diam., bears S. 71° E., 94 lks. dist., with scribe marks ¼ visible on opened blaze.

Remonumentation of Certain Original Corner Points,
T. 6 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

$$\begin{array}{r} T\ 6\ S\ R\ 33\ E \\ \frac{1}{4} \quad \frac{S\ 33}{S\ 4} \\ T\ 7\ S \\ 1977 \end{array}$$

from which a new bearing tree

A pine, 12 ins. diam., bears N. 22° E., 18 lks. dist., mkd. ¼ S33 BT.

Deposit corner stone alongside iron post.

Corner is located 40 lks. south of gravelled road, 20 lks. wide, bears E. and W.

The cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., determined at record bearing and distance from the only remaining original bearing tree:

A pine, 30 ins. diam., bears N. 15° W., 56 lks. dist., with scribe mark S visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} T\ 6\ S\ R\ 33\ E \\ S\ 32\ | \ S\ 33 \\ \hline S\ 5\ | \ S\ 4 \\ T\ 7\ S \\ 1977 \end{array}$$

from which new bearing trees

A grand fir, 13 ins. diam., bears N. 56° E., 160 lks. dist., mkd. T6S R33E S33 BT.

A grand fir, 10 ins. diam., bears S. 9° E., 30 lks. dist., mkd. T7S R33E S4 BT.

A grand fir, 9 ins. diam., bears S. 55° W., 20 lks. dist., mkd. T7S R33E S5 BT.

The ¼ sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp., monumented with the original unmarked granite stone, 16 x 10 x 4 ins., firmly set 4 ins. in the ground, in a collar of stones, from which the remains of the original bearing trees:

A sawed pine stump, 41 ins. diam., bears N. 68° W., 41 lks. dist., with scribe marks BT visible on opened blaze.

A pine snag, 38 ins. diam., bears S. 36° E., 91 lks. dist., with scribe marks BT visible on open blaze.

Remonumentation of Certain Original Corner Points,
T. 6 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 6 S R 33 E
¼ $\frac{S\ 32}{S\ 5}$
T 7 S
1977

from which new bearing trees

A pine, 10 ins. diam., bears N. 14° W., 32 lks. dist., mkd. ¼ S32 BT.

A pine, 10 ins. diam., bears S. 27° W., 47 lks. dist., mkd. ¼ S5 BT.

Deposit corner stone alongside iron post.

The ¼ sec. cor. of secs. 6 and 31, on the S. bdy. of the Tp., monumented with the original unmarked basalt stone, 13 x 10 x 10 ins., firmly set 4 ins. in the ground, in a collar of stones, from which the remains of the original bearing trees:

A pine stump, size indeterminate, bears N. 40° E., 43 lks. dist., with fragmentary scribe marks visible on open blaze. (Record, N. 20° E.)

A decayed pine stump, size indeterminate, bears S. 45° E., 11 lks. dist., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 33 E
¼ $\frac{S\ 31}{S\ 6}$
T 7 S
1977

from which new bearing trees

A fir, 7 ins. diam., bears N. 70° E., 6 lks. dist., mkd. ¼ S31 BT.

A fir, 12 ins. diam., bears S. 45° W., 73 lks. dist., mkd. ¼ S6 BT.

Deposit corner stone alongside iron post.

East Boundary, T. 6 S., R. 33 E.,
Willamette Meridian, Oregon

(Remonumenting a corner established by Frank W. Campbell,
U. S. Deputy Surveyor, in 1883)

The cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., determined at record distance from the remains of the original bearing trees:

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Craig L. Wanless, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of May, 19 57, (I) ~~(We)~~ have remonumented certain original corner points, township 6 south, range 33 east,

of the Willamette Meridian, in the State of Oregon, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 16, 1978
(Date)

Craig L. Wanless
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
~~Washington, D.C.~~
Denver, Colorado

The foregoing field notes of the remonumentation of certain original corner points, township 6 south, range 33 east, Willamette Meridian, Oregon,

executed by Craig L. Wanless, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JAN 23 1980
(Date)

J. J. [Signature]
(Chief, Division of Cadastral Survey)

Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849 626