

INDEX DIAGRAM

Township 6 South, Range 33 East,

6	5	4	3	2	1
	<u>8</u>	<u>7</u>	<u>5</u>		<u>5</u>
7	8	9	10	11	<u>4</u> 12
					<u>3</u>
18	17	16	15	14	13
		<u>6</u>			
19	20	21	22	23	24
30	29	28	27	26	25
	<u>7</u>				
31	32	<u>6</u> 33	34	35	36
<u>3</u>	<u>2</u>	<u>2</u>	<u>1</u>	<u>1</u>	

Remonumentation of Certain Original Corner Points,
T. 6 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

A spruce, 14 ins. diam., bears N. 19° E., 32 lks. dist., with healed blaze.

A spruce snag, 13 ins. diam., bears S. 32° E., 31 lks. dist., with fragmentary scribe marks visible on partially healed blaze. (Record, S. 38° E.)

A spruce snag, 10 ins. diam., bears S. 48° W., 14 lks. dist., with scribe mark R visible on partially healed blaze. (Record, S. 38° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S	
R 33 E	R 34 E
S 12	S 7
S 13	S 18
1977	

from which new bearing trees

A spruce, 9 ins. diam., bears S. 10° E., 52 lks. dist., mkd. T6S R34E S18 BT.

A spruce, 11 ins. diam., bears S. 60° W., 27½ lks. dist., mkd. T6S R33E S13 BT.

A fir, 13 ins. diam., bears N. 67½° W., 79 lks. dist., mkd. T6S R33E S12 BT.

Subdivisions, T. 6 S., R. 33 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by Frank W. Campbell,
U. S. Deputy Surveyor, in 1883)

The ¼ sec. cor. of secs. 11 and 12, monumented with the original unmarked basalt stone, 15 x 10 x 10 ins., loosely set 1 in. in the ground, from which the remains of the original bearing trees:

A larch snag, 12 ins. diam., bears N. 25° E., 42 lks. dist., with scribe marks ¼ S BT visible on open blaze.

A larch snag, 12 ins. diam., bears S. 33° W., 37 lks. dist., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 33 E	
¼	
S 11	S 12
1977	

from which new bearing trees

Remonumentation of Certain Original Corner Points,
T. 6 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

A lodgepole pine, 6 ins. diam., bears N. 75° E.,
14 lks. dist., mkd. ¼ S12 BT.

A lodgepole pine, 6 ins. diam., bears S. 78° W.,
60 lks. dist., mkd. ¼ S11 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 1, 2, 11, and 12, monumented with the
original unmarked basalt stone, 16 x 10 x 10 ins. firmly
set 4 ins. in the ground, from which the remains of the
original bearing trees:

A pine, 33 ins. diam., bears N. 65° E., 44 lks.
dist., with fragmentary scribe marks visible
on open blaze. (Record, 41 lks.)

A pine, 32 ins. diam., bears S. 27° E., 94 lks.
dist., with healed blaze. (Record, 44 lks.)

A pine, 26 ins. diam., bears N. 69° W., 66 lks.
dist., with scribe marks 33E visible on open
blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 6 S R 33 E
S 2 | S 1
S 11 | S 12
1977

from which a new bearing tree

A grand fir, 7 ins. diam., bears S. 39° W., 14½
lks. dist., mkd. T6S R33E S11 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 3, 4, 9, and 10, determined at record
bearing and distance from the remains of the original
bearing trees:

A larch, 22 ins. diam., bears N. 32° E., 25 lks.
dist., with fragmentary scribe marks visible
on open blaze.

A fir snag, 18 ins. diam., bears S. 20° E., 10
lks. dist., with fragmentary scribe marks
visible on partially open blaze.

A fir snag, 25 ins. diam., bears N. 64° W., 24
lks. dist., with fragmentary scribe marks visible
on partially open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 6 S R 33 E
S 4 | S 3
S 9 | S 10
1977

Remonumentation of Certain Original Corner Points,
T. 6 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

from which new bearing trees

A grand fir, 10 ins. diam., bears S. $39\frac{1}{2}^{\circ}$ E., 53 lks. dist., mkd. T6S R33E S10 BT.

A grand fir, 12 ins. diam., bears S. 26° W., 56 lks. dist., mkd. T6S R33E S9 BT.

A grand fir, 13 ins. diam., bears N. $23\frac{1}{2}^{\circ}$ W., 90 lks. dist., mkd. T6S R33E S4 BT.

Set a 5 ft. steel fence post alongside iron post.

Corner is located 22 lks. south of wire fence extending E. and W.

The $\frac{1}{4}$ sec. cor. of secs. 32 and 33, monumented with the original unmarked granite stone, 18 x 10 x 10 ins., firmly set 4 ins. in the ground, from which the remains of the original bearing trees:

A pine, 32 ins. diam., bears S. 55° E., 53 lks. dist., with healed blaze. (Record, S. 62° E., 49 lks.)

A sawed larch stump, 17 ins. diam., bears N. 22° W., 20 lks. dist., with scribe mark S visible on opened blaze. (Record, N. 33° E.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 33 E

$\frac{1}{4}$
S 32 | S 33
1977

from which a new bearing tree

A pine, 18 ins. diam., bears N. 29° W., 37 lks. dist., mkd. $\frac{1}{4}$ S32 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 16, 17, 20, and 21, monumented with the original unmarked basalt stone, 15 x 12 x 12 ins., firmly set 6 ins. in the ground, in a collar of stones, from which the remains of the original bearing trees:

A root hole, bears N. 18° E., 52 lks. dist., with a down pine alongside, 16 ins. diam., with scribe marks R33E S16 BT visible on open blaze.

A juniper snag, 14 ins. diam., bears S. 40° W., 156 lks. dist., with scribe marks T6S R33E S20 visible on open blaze.

A pine, 21 ins. diam., bears N. 73° W., 39 lks. dist., with scribe marks R33E S visible on open blaze.

At the corner point

Remonumentation of Certain Original Corner Points,
T. 6 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 6 S R 33 E
S 17 | S 16
S 20 | S 21
1977

from which new bearing trees

A pine, 20 ins. diam., bears N. 11° E., 51 lks. dist., mkd. T6S R33E S16 BT.

A pine, 12 ins. diam., bears S. 68½° E., 107 lks. dist., mkd. T6S R33E S21 BT.

A pine, 15 ins. diam., bears S. 32° W., 62 lks. dist., mkd. T6S R33E S20 BT.

Deposit corner stone alongside iron post.

The ¼ sec. cor. of secs. 4 and 9, determined at record bearing and distance from the remains of the original bearing trees:

A decayed pine stump, size indeterminate, bears N. 20° W., 30 lks. dist., no marks visible.

A larch snag, 11 ins. diam., bears S. 54° W., 13 lks. dist., with scribe marks ¼ S visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 33 E
¼ S 4
S 9
1977

from which new bearing trees

A grand fir, 9 ins. diam., bears N. 12½° W., 80 lks. dist., mkd. ¼ S4 BT.

A grand fir, 8 ins. diam., bears S. 39° W., 45½ lks. dist., mkd. ¼ S9 BT.

Set a 5 ft. steel fence post alongside iron post.

Corner is located 18 lks. S. 30° W. of fence corner, fences extend E., W., and N.

The cor. of secs. 29, 30, 31, and 32, determined at record bearing and distance from the remains of the original bearing trees:

A decayed pine stump, size indeterminate, bears S. 33° E., 38 lks. dist., with scribe marks T6S R33E S32 BT visible on open blaze.

Remonumentation of Certain Original Corner Points,
T. 6 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

A pine snag, 26 ins. diam., bears S. 44° W., 105 lks. dist., with scribe marks BT visible on open blaze.

A root hole, bears N. 82° W., 107 lks. dist., with a down pine alongside, 44 ins. diam., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 33 E
S 30 S 29
S 31 S 32
1977

from which new bearing trees

A grand fir, 12 ins. diam., bears N. 33° E., 23 lks. dist., mkd. T6S R33E S29 BT.

A grand fir, 8 ins. diam., bears S. 34° E., 29½ lks. dist., mkd. T6S R33E S32 BT.

A grand fir, 13 ins. diam., bears S. 51° W., 46 lks. dist., mkd. T6S R33E S31 BT.

A grand fir, 11 ins. diam., bears N. 65° W., 21 lks. dist., mkd. T6S R33E S30 BT.

The cor. of secs. 5, 6, 7, and 8, monumented with the original unmarked basalt stone, 12 x 8 x 7 ins., loosely set in a mound of stone, 2 ft. base, 1 ft. high, from which the remains of the original bearing trees:

A pine stump, 18 ins. diam., bears N. 58° E., 32 lks. dist., with healed blaze.

A fir, 27 ins. diam., bears S. 24° E., 44 lks. dist., with fragmentary scribe marks visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 6 S R 33 E
S 6 S 5
S 7 S 8
1977

from which new bearing trees

A grand fir, 8 ins. diam., bears N. 53½° E., 37 lks. dist., mkd. T6S R33E S5 BT.

A pine, 20 ins. diam., bears S. 71° W., 51 lks. dist., mkd. T6S R33E S7 BT.

A grand fir, 12 ins. diam., bears N. 53° W., 50 lks. dist., mkd. T6S R33E S6 BT.

Remonumentation of Certain Original Corner Points,
T. 6 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

Deposit corner stone and set a 5 ft. steel fence
post alongside iron post.

Corner is located 2 lks. north of wire fence extending
E. and W.

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Craig L. Wanless, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of May, 19 57, (I) ~~(We)~~ have remonumented certain original corner points, township 6 south, range 33 east,

of the Willamette Meridian, in the State of Oregon, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 16, 1978
(Date)

Craig L. Wanless
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
~~Washington, D.C.~~
Denver, Colorado

The foregoing field notes of the remonumentation of certain original corner points, township 6 south, range 33 east, Willamette Meridian, Oregon,

executed by Craig L. Wanless, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JAN 23 1980
(Date)

J. J. [Signature]
(Chief, Division of Cadastral Survey)

Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849 626