

Subdivisions of T. 1 N., R. 36 E.

Chains	
37.50	Top of ridge, about 400 ft. above creek, course S.E.
40.00	Set a basalt stone, 15x12x6 ins., 10 ins. in the ground, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, and raised a mound of stone alongside.
46.00	Bottom of gulch about 250 ft. below ridge, course S.E.
77.00	Top of ridge, about 500 ft. above gulch, course S.E.
80.00	Set a basalt stone, 20x12x3 ins., 15 ins. in the ground, for cor. to secs. 23, 24, 25 and 26, marked with 2 notches on S. and 1 notch on E. edges, and raised a mound of stone alongside.
	Land, mountainous.
	Soil, sandy loam and stony, 2nd and 3rd rate.
	Timber, scattering fir, pine and tamarack.
	East on a random line between secs. 24 and 25.
	Var. 19°E.
	Descend about 500 ft. to
23.00	Dry bed of creek, course S.E.
40.00	Set temporary $\frac{1}{4}$ sec. cor.
49.00	Top of ridge about 400 ft. above creek bed, course S.
	Descend about 800 ft. to
80.30	Intersect E. boundary 25 lks. S. of the cor. to secs. 24, 25, 19 and 30, which is 4 flat stones laid flat ways on each other marked with a † on top and T 1 N S 19 on N.E., R 37 E S 30 on S.E., R 36 E S 25 on S.W., and S 24 on N.W. angles of † from which, A pine, 18 ins. diam., bears S. 28°W., 78 lks. dist., marked T 1 N R 36 E S 25 B T.
	Thence I run
	S. 89°49'W. on a true line between secs. 24 and 25.
40.15	Set a basalt stone, 14x6x6 ins., 9 ins. in the ground, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face, and raised a mound of stone alongside.
80.30	The cor. to secs. 23, 24, 25 and 26.
	Land, mountainous.
	Soil, stony, 3rd rate. Timber, scattering pine and fir.