

## Subdivisions of T. 1 N., R. 37 E.

Chains	<p>From the cor. to secs. 31 and 32 on the Base Line, which is a post, 4 ins. square, marked B L T 1 N R 37 E on N. S 32 on E. and S 31 on W. faces, with 5 notches on E. and 1 notch on W. faces, from which,</p> <p>A fir, 10 ins. diam., bears N.80°E., 50 lks. dist., marked T 1 N R 37 E S 32 B T.</p> <p>A pine, 10 ins. diam., bears S.5°E., 46 lks. dist., marked T 1 S R 37 E S 6 B T.</p> <p>A fir, 7 ins. diam., bears N.20°W., 72 lks. dist., marked T 1 N R 37 E S 31 B T.</p> <p>I run North between secs. 31 and 32. Var. 20½°E. Through timber.</p> <p>1.00 Dry bed of creek, 25 lks. wide, runs N.W.</p> <p>5.00 Ascend hill about 200 ft. to</p> <p>29.00 Top of ridge, course N.W.</p> <p>34.50 Bottom of gulch, about 200 ft. below ridge. A creek, 6 lks. wide, runs N.W.</p> <p>40.00 Set a basalt stone, 16x7x5 ins., 11 ins. in the ground, for ¼ sec. cor. marked ¼ on W. face, from which, A pine, 14 ins. diam., bears S.75°E., 39 lks. dist., marked ¼ S B T. A pine, 7 ins. diam., bears N.15°W., 55 lks. dist., marked ¼ S B T.</p> <p>61.50 Top of ridge about 250 ft. above creek, course W.</p> <p>68.50 Bottom of gulch, about 100 ft. below ridge, course W.</p> <p>80.00 Set a basalt stone, 15x8x5 ins., 10 ins. in the ground, for cor. to secs. 29, 30, 31 and 32, marked with 1 notch on S. and 5 notches on E. edges, from which, A fir, 24 ins. diam., bears N.5°E., 60 lks. dist., marked T 1 N R 37 E S 29 B T. A fir, 7 ins. diam., bears S.80°W., 77 lks. dist., marked T 1 N R 37 E S 31 B T. A fir, 20 ins. diam., bears N.20°W., 77 lks. dist., marked T 1 N R 37 E S 30 B T.</p> <p>No other tree within limits.</p>
--------	--