

T. 1 S., R. 34 E., W.M.

Chains		Feet
40.00	Set a basalt stone, 10 x 10 x 7 ins., 7 ins. in ground for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face. Raised mound of stone alongside. Pits impracticable.	100
54.00	Brook, 15 lks. wide, course N.	900
79.50	Top of mountain	1500
80.00	Set a basalt stone, 10 x 10 x 10 ins., 7 ins. in ground for Cor. to Secs. 2, 3, 34 & 35, marked two notches on E. and 4 on W. edges. Raised mound of stone alongside. Pits impracticable.	
	Land; mountainous, 80.00 chs.	
	Scattering pine timber in canyons.	
	Soil; 4th rate.	
	S. 89° 25' W. on S. Bdy. Sec. 34	
	Var. 22° E.	
39.00	Creek, 20 lks. wide	900
40.00	Set basalt stone, 12 x 10 x 5 ins., 8 ins. in ground for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. Face. Raised mound of stone alongside. Pits impracticable.	
78.00	Summit of ridge, course N.	1200
80.00	Set basalt stone, 20 x 12 x 8 ins., 15 ins. in ground for Cor. to Secs. 3, 4, 33 & 34, marked 3 notches on E. and W. edges. Raised mound of stone alongside. Pits impracticable.	
	Land; mountainous, 80.00 chs.	
	Soil; 4th rate.	
	Scattering pine timber in canyons.	
	S. 89° 25' W. on S. Bdy. of Sec. 33.	
	Var. 19° 30' E.	
14.59	Bottom of ravine, course N.	300
22.00	Top of ridge, course N.	300
39.00	Creek, 20 lks. wide, course N.E.	1000
40.00	Set basalt stone, 10 x 8 x 8 ins., 7 ins. in ground for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face, from which, A pine, 12 ins. diam., brs. N. 78° E., 38 lks. dist.	