

Subdivisional Lines, T.1 S., R.36 E., W.M.

Chains		Feet
	Through timber.	
40.00	A tamarack, 5 ins. diam., which I mark $\frac{1}{4}$ S on W. face, for $\frac{1}{4}$ Sec. Cor., from which, A tamarack, 5 ins. diam., brs. S.45°E., 9 lks. dist., marked $\frac{1}{4}$ S., B.T. A tamarack, 5 ins. diam., brs. N.40°W., 13 lks. dist., marked $\frac{1}{4}$ S., B.T.	
80.00	Set basalt stone, 12 x 10 x 10 ins., 8 ins. in ground for Cor. to Secs. 27 & 28, 33 & 34, marked with 1 notch on S. and 3 notches on E. edges, from which, A pine, 13 ins. diam., brs. N.35°E., 62 lks. dist., marked T.1 S., R.36 E., S.27, B.T. A tamarack, 20 ins. diam., brs. S.65°E., 154 lks. dist., marked T.1 S., R.36 E., S.34, B.T. A pine, 24 ins. diam., brs. S.85°W., 118 lks. dist., marked T.1 S., R.36 E., S.33, B.T. A pine, 9 ins. diam., brs. N.30°W., 32 lks. dist., marked T.1 S., R.36 E., S.28, B.T.	
	Land; mountainous.	
	Soil; sandy loam, 2nd rate.	
	Heavily timbered with fir, tamarack and pine.	
	E. on a random line bet. Secs. 27 & 34. Var. 20 $\frac{1}{2}$ °E.	
	Through timber.	
40.00	Set temp. $\frac{1}{4}$ Sec. Cor.	
63.00	Descend about 200 ft. to	
80.64	Intersect, 42 lks. N. of the Cor. to Secs. 26, 27, 34 & 35. Thence I run N.89°42' W. on a true line bet. Secs. 27 & 34.	
40.32	Set basalt stone, 24 x 12 x 10 ins., 10 ins. in ground for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face, from which, A pine, 4 ins. diam., brs. N.25°W., 34 lks. dist., marked $\frac{1}{4}$ S., B.T. A tamarack, 4 ins. diam., brs. S.60°W., 17 lks. dist., marked $\frac{1}{4}$ S., B.T.	