

Retracement-Resurvey of Subdivisions, T. 2 N., R. 33 E.

Chains	
	entitled to be accepted as such. I find no trace of the original bearing tree or other evidence of the old cor.
	Land, level bottom.
	Soil, rich loam and gravel bar underlaid with gravel, 1st and 3rd rate.
	Timber, cottonwood.
	Undergrowth, willow, thorn, clematis and cottonwood.
	From the point for cor. of secs. 3, 4, 9 and 10. S.0°31'W., resurveying line bet. secs. 9 and 10. Over gravel bar.
4.94	Leave bar; over bottom land, bears E. and W.
22.69	Center of O.W.R.R. and N. Ry., bears N.85°16' W. and S.85° 16' E.
40.58	Intersect the $\frac{1}{4}$ sec. cor. as reestablished by the county surveyor, which is a water worn basalt stone, firmly set below the surface of the ground at intersection of roads extending in cardinal directions, marked X on top and $\frac{1}{4}$ on W. face. At a point S.66°E., 110 lks. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for witness cor. to the $\frac{1}{4}$ sec. cor., with brass cap marked WC $\frac{1}{4}$ S9 S10 1917 from which A cottonwood, 22 ins. diam., bears N.40°15'E., 105 lks. dist., marked W C $\frac{1}{4}$ S 10 B T. A cottonwood, 18 ins. diam., bears S.41°45'W., 170 $\frac{1}{2}$ lks. dist., marked W C $\frac{1}{4}$ S 9 B T. Thence S.0°25'E., continuing my measurements.
46.19	Brock, 4 lks. wide, course N.75°W.
80.82	Intersect the cor. of secs. 9, 10, 15 and 16, which is a