

Subdivisions, T. 2 N., R. 36 E.

chains	
	secs. 3, 4, 33 and 34, which is a decayed post, marked and witnessed as described by the Surveyor General. I replace the post by a basalt stone 20 x 12 x 8 ins., 15 ins. in the ground marked with 3 notches on E. and W. edges.
	Set basalt stone, 15 x 8 x 8 ins., 10 ins. in the ground for closing cor. of secs. 3 and 4, marked with C.C. on S. face and with 3 notches on E. and W. faces, from which
	A fir, 22 ins. in diam., bears S. 40° E., 18 lks. dist., marked T. 2 N., R. 36 E., S.3, B.T.
	A fir, 36 ins., bears S. 60° W., 44 lks. dist., marked T.2 N., R. 36 E., S.4, B.T.
	I destroy all marks on old cor., pertaining to the survey S.
	From the closing corner, I run,
	S. 0° 03' E. on true line bet. secs. 3 and 4.
	Ascend along E. slope of mountain through heavy pine and fir timber.
15.91	A fir, 36 ins. in diam. on line, I mark with 2 notches on N. and S. edges.
26.25	Enter scattering timber, bears E. and W.
28.50	Ravine, 150 ft. deep, course N. 70° E.
	A large spring in ravine, just W. of line.
30.78	Set a fir post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S. 4 on W. face and S. 3 on E. face, from which
	A pine, 16 ins. in diam., bears N. 3 $\frac{1}{2}$ ° E., 49 lks. dist., marked $\frac{1}{4}$ S. B. T.
	A fir, 36 ins. in diam. bears S. 75° W., 18 lks. dist., marked $\frac{1}{4}$ S. B. T.
47.00	Ravine, 150 ft. deep, course N. 60° E.
	Top of branch ridge point, bears E.
70.78	The cor. of secs. 3, 4, 9 and 10.
	Land, mountainous.