

Subdivisions T. 2 N. R. 37 E. W. M.

chains  
77.00

Creek 5 lks. wide, slow current, course N. 48° W.

Ascend gradually.

80.00

Set basalt stone, 15x10x6 ins. 10 ins. in the ground, for cor. of Secs. 25, 26, 35, and 36, marked with 1 notch on S. and E. edges; from which

A spruce, 18 ins. diam., bears N 55° E 35 lks. dist., marked T 2 N R 37 E S 25 B T.

A tamarack, 36 ins. diam., bears S 10° E 82 lks. dist., marked T 2 N R 37 E S 36 B T.

A fir, 18 ins. diam., bears S 52° W 106 lks. dist., marked T 2 N R 37 E S 35 B T.

A fir, 10 ins. diam., bears N 70° W 55 lks. dist., marked T 2 N R 37 E S 26 B T.

Land, mountainous.

Soil sandy loam and stony. 2nd and 3rd rate.

Timber, pine, fir, tamarack and spruce.

Mountainous land, 80.00 chs.

W on Sectional Correction Line bet. Secs. 26 and 35

Ascend through heavy timber and undergrowth.

1.25 Trail to Bingham Springs, course S. 45° W., N. 20° E.

6.50 Enter sheep corral, bears N. and S.

9.50 Leave sheep corral, bears N. and S.

20.00 Ascend gradually over mountain prairie.

28.25 Leave heavy timber, bears N. and S.

29.00 Descend W. slope into Thomas and Ruckel Creek.

30.00 Abrupt descent.

Enter scattering timber bears N. 10° W., S. 30° E.

32.00 Enter old burn, bears N. and S.

40.00 Set ironstone, 18x8x6 ins. 12 ins. in the ground, for

$\frac{1}{4}$  Secs., cor., marked  $\frac{1}{4}$  on N. face; from which

A fir 28 ins. diam., bears S 24° E 204 lks.

dist., marked  $\frac{1}{4}$  S 35 B T.

No other tree in limit, Raise mound of stone 2 ft.