

Subdivisions T. 2 N. R. 37 E. W. M.

Chains	
	W. of Sectional Correction Line, bet. Secs. 28 and 33. Descend steep S. slope through heavy timber.
5.00	Enter scattering timber bears N. 60° E., S. 60° W.
14.00	A fir, 28 ins. diam., on line, I mark 2 notches on E. and W. faces.
24.85	Spring branch, 2 lks., wide course N. 60° W. Pass along steep N. slope of hill.
40.00	Set basalt stone, 15x10x6 ins, 10 ins., in the ground for $\frac{1}{4}$ Sec. cor. marked $\frac{1}{4}$ on N. face; from which A fir, 24 ins. diam., bears N. 50° E 30 lks. dist., marked $\frac{1}{4}$ S. 28 B T. A fir, 12 ins. diam. bears S 75° W 31 lks. dist., marked $\frac{1}{4}$ S 33 B T.
41.00	Leave heavy timber and enter old burn, bears N. and S. 10° W. Very densely overgrown.
48.80	Foot of hill, 800 ft. below Sec. cor. Creek, 8 lks. wide; Swift current, course N. 30° W. Ascend steep E. slope.
58.25	Top of ridge, 300 ft. above creek, course N. and S. Descend.
59.00	Enter heavy pine timber, bears N. 30° E. S., 30° W. Leave old burn.
65.00	Pass through forest fire.
70.00	Leave raging fire, bears N. and S. 30° W.
76.25	Ironstone dyke, 20 ft. high, bears N. 20° W., S. 20° E. Leave timber.
79.50	Creek, 10 lks. wide, swift current, course N. 85° E. Up creek bottom, over large boulders.
80.00	The true point for Sec. cor. falls on a large boulder in place, 5x4x3 ft. above ground, on which I cut a cross at the exact cor. point, for cor. of Secs. 28, 29, 32 and 33. Mark 4 notches on E. and 1 notch on S. edges. No trees in limits. Raise mound of stone 3 ft. base, 2 ft. high W. of cor. point. Pits imprac- ticable. Land Mountainous.