

Subdivisions T. 2 R. 37 E. W. M.

Chains	<p>Soil, stony 3rd rate. Timber, pine, fir, spruce, tamarack and alder. Undergrowth, firs, laurel and willow. Mountainous land. 80.00 chs. July 15, 1901. W. on Sectional Correction Line bet. Secs. 29 and 32</p>
0.65	<p>Up creek bottom over large boulders and ascend N. slope. Leave creek bears N. 85° E., S. 50° W., and ascend steep E. slope</p>
1.00	<p>Enter scattering timber and undergrowth, bears N. 30° E., S. 30° W.</p>
14.25	<p>Ridge point, bears N. 60° E., S. 60° W.</p>
15.00	<p>Enter heavy timber, bears N. 60° E., S. 60° W. More gradual ascent along N. slope of ridge.</p>
28.00	<p>Dry bed of stream, 5 lks wide, course N. 60° E.</p>
40.00	<p>Set basalt stone, 20x12x8 ins. 15 ins. in the ground, for $\frac{1}{4}$ Sec. cor., marked $\frac{1}{4}$ on N. face; from which A fir, 16 ins. diam., bears N 80° E 92 lks. dist., marked $\frac{1}{4}$ S. 29 B T. A fir, 12 ins. diam., bears S 25° E 49 lks. dist., marked $\frac{1}{4}$ S 32 B T.</p>
41.00	<p>Over rolling ground on Goodwin Ridge.</p>
80.00	<p>Set fir post, 3 ft. long 4 ins. sq., 24 ins. in the ground for cor. of Secs. 29, 30, 31 and 32, marked T. 2 N. S. 29, on N. E., R. 37 E., S. 32., on S. E., S. 31 on S. W., and S. 30 on N. W. faces, with 5 notches on E. and 1 notch on S. edges; from which A fir, 20 ins. diam., bears N 46° E 24 lks. dist., marked T 2 N R 37 E S 29 B T. A spruce, 12 ins. diam., bears S 40° E 4 lks. dist., marked T 2 N R 37 E S 32 B T. A spruce 24 ins. diam., bears S 53° W 8 lks. dist., marked T 2 N R 37 E S 31 B T.</p>