

Subdivisions of T. 2 N. R. 37 E. W. M.

Chains	
	N. 0° 2' W. bet. Secs. 22 and 23. Descend through heavy timber and dense undergrowth.
5.50	Foot of mountain bears N. W., S. E. Over better land not subject to inundation.
7.15	Thomas and Ruckel Fork Umatilla River, 15 lks. wide, swift current, in canyon 850 ft. deep, course N. 40° W.
9.75	Ascend steep S. slope of mountain.
12.00	Enter scattering timber, bears E. and W.
13.00	Leave dense undergrowth, bears E. and W.
35.75	Top of ridge, 500 ft. above creek, bears E. and W. Descend along W. slope of main divide.
37.00	Enter dead thicket, bears E. and W.
40.00	Set basalt stone, 15x10x8 ins. 10 ins. in the ground for $\frac{1}{4}$ Sec. cor., marked $\frac{1}{4}$ on W. face, from which A tamarack, 6 ins. diam., bears N. 36° E., 197 lks. dist., marked $\frac{1}{4}$ S 23 B T. A tamarack, 8 ins. diam., bears S. 41° W., 120 lks. dist., marked $\frac{1}{4}$ S 22 B T.
43.00	Leave dead thicket, bears W. and E.
43.25	Ravine 150 ft. deep, course W. Ascend along W. slope.
45.00	Enter heavy timber, bears N. 30° W., S. 70° E.
53.25	Small spring in ravine, runs S. 60° W. Steep ascent.
61.25	Enter scattering timber, bears E. and W. More gradual ascent.
75.00	Top of ridge, 200 ft. high, bears N. 80° W., S. 80° E.
75.75	Enter heavy timber, bears E. and W.
80.00	A fir, 40 ins. diam., for cor. of Secs. 14, 15, 22 and 23, I mark T 2 N. R. S. 14 on N E., R 37 E S 23 on S E S 22 on S W and S 15 on N W faces; with 2 grooves on E. and 3 grooves on S. sides, from which A fir, 24 ins. diam., bears N. 64° E., 17 lks. dist., marked T 2 N R 37 E S 14 B T.