

Subdivisions of T. 2 N. R 37 E. W. M.

Chains	
0.10	N. 0° 04' W. bet. Secs. 28 and 29. Leave N. bank of creek, course N. 85° E., and ascend steep S. slope through scattering and dense undergrowth.
5.60	Intersect great iron stone dyke, 50 ft. high, bears N. 20° W., S. 20° E.
20.00	Ridge point, 300 ft. above creek, bears E. Descend along steep E. slope of mountain.
25.00	Enter heavy timber, bears E. and W.
37.50	Foot of ravine, 100 ft. deep, bears N. 80° E. Spring just above line.
40.00	A fir, 12 ins. diam., for $\frac{1}{4}$ Sec. cor., marked $\frac{1}{4}$ S. 29, on W. and S. 28 on E. faces, from which A fir, 12 ins. diam., bears S. 21° E., 23 lks. dist., marked $\frac{1}{4}$ S B W. A fir, 16 ins. diam., S. 5° W., 19 lks. dist., marked $\frac{1}{4}$ S B T.
51.00	Leave undergrowth and enter heavy fir forest, bears E. and W.
66.80	Spring branch, 2 lks. wide, course N. 60° E.
70.25	Over perpendicular bluff 20 ft. high.
80.00	Set basalt stone, 20x10x4 ins., 15 ins. in the ground for cor. of Secs. 20, 21, 28 and 29, marked with 4 notches on E. and 2 notches on S. edges, from which A fir, 16 ins. diam., bears N. 24° E., 37 lks. dist., marked T 2 N R 37 E., S 21 B T. A fir, 16 ins. diam., bears S. 70° E., 17 lks. dist., marked T 2 N R 37 E., S 28 B T. A fir, 12 ins. diam., bears S. 55° W., 12 lks. dist., marked T 2 N R 37 E., S 29 B T. A fir, 24 ins. diam., bears N. 50° W., 23 lks., dist., marked T 2 N R 37 E., S 20 B T.
	Lead Mountainous. Soil, stony and loam; 3rd and 2nd rate. Timber, fir, pine, spruce, tamarack and yew.