

Subdivisions of T. 2 N. R. E. W. M.

Chains	W. on random line bet. Secs. 18 and 19.
40.00	Set temp. $\frac{1}{4}$ Sec. cor.
100.85	Intersect W. bdy. of Tp. 4.44 chs. S. of the cor. of Secs. 13, 18, 19 and 24, described heretofore.
	I destroy all marks on old cor. pertaining to the survey E..
	At point of intersection set basalt stone, 15x10x8 ins., 10 ins. in the ground, for closing cor. of Secs. 18 and 19, marked C C on E. face; with 3 grooves on N. and S faces, from which
	A fir, 10 ins. diam., bears N. 89° E. 15 lks. dist., marked T 2 N R 37 E., S 18 B T.
	A fir, 10 ins. diam., bears S. 87° E., 11 lks. dist., marked T 2 N R 37 E., S 19 B T.
	Thence I run E. on true line bet. Secs. 18 and 19. Ascend steep W. slope of mountain through scattering timber.
23.00	Top of ridge, 400 ft. above closing cor. bears N. W. and S. E.
25.50	Enter heavy timber and dense undergrowth, bears N. and S. Descend gradually.
42.50	Creek, 3 lks. wide, course N. 60° W. Ascend S. W. slope of ridge, bears N. W. S. E.
55.00	Top of ridge, 200 ft. above creek, bears N. and S.
60.85	A fir, 10 ins. diam., for $\frac{1}{4}$ Sec. cor. I mark $\frac{1}{4}$ S 18 on N. and S 19 on S. faces, from which
	A fir, 16 ins. diam., bears N. 80° W., 34 lks. dist., marked $\frac{1}{4}$ S 18 B T.
	A fir, 24 ins. diam., bears S. 11° W. 34 lks. dist., marked $\frac{1}{4}$ S 19 B T.
70.65	Spring branch, 2 lks. wide, in ravine 50 ft. deep, course N. W.
90.35	Top of ridge, 400 ft. above creek, bears N. and S.