

N. Bdy., T. 3 S., R.33 E., W.M.

Chains		Feet
74.85	Creek, 10 lks. wide, in canyon, course N., 1000 ft. deep. Ascend.	
80.00	Set basalt stone, 14 x 8 x 7 ins., 10 ins. in ground, for Cor. to Secs. 2, 3, 34 & 35, marked with 2 notches on E. and 4 notches on W. edges and raised mound of stone alongside, from which, A pine, 10 ins. diam., brs. S.51° W., 110 lks. dist., marked T.3 S., R.33 E., S. 3, B.T. A fir, 6 ins. diam., brs. N.13° E., 72 lks. dist., marked T.2 S., R.33 E., S.35, B.T. A fir, 6 ins. diam., brs. N. 20° W., 59 lks. dist., marked T.2 S., R.33 E., S.34, B.T. 300 ft. above Creek on steep hillside. Land; broken and mountainous. Heavily timbered with pine, fir and tamarack timber on E. 45 chs. with dense undergrowth of pine and fir, etc.	
	W. on N. Bdy. of Sec. 3.	
		Var. 18° 30' E.
.60	Enter fir timber, brs. N. & S.	
10.50	Leave timber, brs. N.E. & S.W.	
25.75	Top of rocky ridge, brs. N. & S., 1000 ft. above Sec. Cor. Descend.	
40.00	Set basalt stone, 15 x 9 x 7 ins., 10 ins. in ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face, from which, A fir, 34 ins. diam., brs. N.7° W., 65 lks. dist., marked $\frac{1}{4}$ S., B.T. A fir, 20 ins. diam., brs. S.19° W., 39 lks. dist., marked $\frac{1}{4}$ S., B.T.	
	600 ft. below top of ridge.	
41.00	Enter timber, brs. N.W. & S.E.	
53.50	Leave timber, brs. N. & S.	
80.00	Set basalt stone, 15 x 12 x 7 ins., 10 ins. in ground, for Cor. to Secs. 3, 4, 33 & 34, marked with 3 notches on the E. & W. edges and raised mound of stone along- side. Pits impracticable, from which	