

Exterior & Subdivisional Lines, T.2 S., R.33 E., W.M.

Chains		Feet
	Land; mountainous, 137.60 chs. Soil; stony 5th rate. Timber; pine, fir & tamarack, 98.10 chs.	
	S. bet. Secs. 31 & 32. Descend 35° Var. 19°45'E.	
6.00	Gulch, course W. Ascend 25°.	-300
14.00	Summit of ridge falls W. Descend 28°.	+200
21.00	Canyon, course W. Ascend 35°.	-210
31.50	Summit of ridge falls W. Descend 35°.	+230
40.00	Set basalt stone, 16 x 7 x 5 ins., 6 ins. in ground (digging impracticable) for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face. Raised mound of stone, 1 $\frac{1}{2}$ ft. high x 3 $\frac{1}{2}$ ft. base over Cor., on S. hillside. Pits impracticable.	
43.75	Canyon, course W. Enter timber. Ascend 30°	-300
53.25	Intersect S. Bdy. of Tp., 825 lks. E. of Cor. to Secs. 3, 4, 33 & 34, which is a basalt stone, 1 $\frac{1}{2}$ ft. high x 2 $\frac{1}{2}$ ft. base, alongside, from which, A willow, 6 ins. diam., brs. S.W., 16 lks. dist., marked T 3 S., R.33 E., S.4, B.T. At point of intersection, I Set basalt stone, 18 x 10 x 6 ins., 6 ins. in ground, for Closing Cor. (Digging impracticable), to Secs. 31 & 32, marked 5 notches on E. Cor., 1 notch on W. face, & C.C. on N. face. Raised mound of stone, 1 $\frac{1}{2}$ ft. high x 3 $\frac{1}{2}$ ft. base over Cor., which is 3 ft. S. of a loose rock of the weight of about 1000 lbs., from which Cor., A fir, 24 ins. diam., brs. N.80°E., 74 lks. dist., marked T.2 S., R.33 E., S.32, B.T. A fir, 6 ins. diam., brs. N.72°W., 200 lks. dist., marked T.2 S., R.33 E., S.31, B.T. Var. 18°45'E.	
	Land; mountainous & stony, 53.25 chs. Timber; pine, fir & tamarack, 9.50 chs. Soil; 4th rate.	
	Sept. 28, 1891.	