

Resurvey portion E. Bdy., T.2 S., R.34 E., W. M.

Chains		Feet
	Soil; light loam on basalt bedrock, 2nd rate. Timber; pine, tamarack & fir. Undergrowth; pine, fir and willow.	
	<hr/>	
	N., resurveying the line bet. Secs. 1 & 6. Ascend gradually through scattering timber.	
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ Sec. Cor., with brass cap, marked,	
	$\begin{array}{c} \uparrow \\ S1 S6 \\ 1917 \end{array}$	
	from which, A fir, 16 ins. diam., brs. N.80°E., 6 lks. dist., marked $\frac{1}{4}$ S.6, B.T. A fir, 16 ins. diam., brs. S.7°30'W., 43 lks. dist., marked $\frac{1}{4}$ S1, B.T.	
	The old $\frac{1}{4}$ Sec. Cor., brs. N.39°45'E., 85 lks. dist., which I destroy.	
41.00	Leave timber; enter glade, brs. N.W. & S.E.	
50.00	Top of ascent, brs. N.W. & S.E.; descend .460 ft., through scattering timber and dense undergrowth.	
76.32	Ravine, course N.E.; ascend S.E. slope.	
80.82	Intersect the point for Cor. of Tps. 1 & 2 S., Rs. 34 & 35 E., as determined by reference to the N.E. bearing tree. This point is on a steep E. slope, where it is impracticable to set an iron post, more than 6 ins. in ground; therefore, at a point 30 lks. W. of true Cor., point Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in ground, for witness Cor. to the Cor. to Tps. 1 & 2 S., Rs. 34 & 35 E., with brass cap, marked,	
	$\begin{array}{c} T1S \\ R34E R35E \\ S36 S31 \\ \hline S1 S6 \\ R34E R35E \\ T2S \\ 1917 \end{array}$	
	and raise mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, S. of post. From the true Cor. point A pine, 12 ins. diam., brs. N.26°E., 112 lks. dist.,	