Re-survey Subdivisional Lines, T. 2 S.,R.34 E.,W. M.

Chains		Feet
	marked T.2 S.,R.34 E.,S.3,B.T.	

A fir, 10 ins. diam., brs. S.87°E., 115 lks. dist.,

marked T.2 S.,R.34 E.,S.10,B.T.

A fir, 9 ins. diam., brs. S.89°30'W., 105 lks. dist.,

marked T.2 S.,R.34 E.,S.9,B.T.

A fir, 8 ins. diam., brs. N.61°W., 23 lks. dist.,

marked T.2 S.,R.34 E.,S.4,B.T.

From the Cor. of Secs. 9, 10, 15 & 16.

N.0°39'W., resurveying the line bet. Sec. 9 & 10.

Over mountainous land, through scattering timber.

39.84 Intersect the ¼ Sec. Cor., which is basalt stone, 18 x 12 x

6 ins., above ground, marked ¼ on W. face.

At point 1 lk. W. of Cor.

Set iron post, 3 ft. long, 1 in. diam., 26 ins. in ground,

for witness Cor. to ¼ Sec. Cor., with brass cap,marked,

$$\frac{1}{4}$$
S9 | S10   WC
1917

from which,

A fir, 8 ins. diam., brs. S.8°E., 54½ lks. dist.,

marked ¼ S.10,B.T.

A fir, 6 ins. diam., brs. S.77°30'W., 36 lks. dist.,

marked ¼ S.9,B.T.

Thence

N.1°07'E., continuing my measurements.

Ascend broken S.E. slope, 225 ft. to

73.45 Top of spur, slopes W., enter dense undergrowth, brs.E.&

W., and descend 165 ft. to

80.07 The Cor. of Secs. 3, 4, 9 & 10.

Land; mountainous.

Soil; rocky, 3rd rate.

Timber; very scattering pine & fir.

Undergrowth; willow.

N.0°02'W., resurveying the line bet. Secs. 3 & 4.

Descend 950 ft. over steep broken N.W. slope, through dense