

Retracement East Bdy., T.2 S., R.34 E., W.M.

Chains		Feet
	<p>with brass cap, marked,</p> <p style="text-align: center;"> $\frac{1}{4}$ S24 S19 1917 </p> <p>from which,</p> <p>A pine, 20 ins. diam., brs. N.73°30'E., 83 lks. dist., marked $\frac{1}{4}$ S., B.T. (Old B.T.)</p> <p>A pine, 20 ins. diam., brs. N.81°30'W., 164 lks. dist., marked $\frac{1}{4}$ S., B.T. (Old B.T.)</p> <p>The true course & dist. of this line to the $\frac{1}{4}$ Sec. Cor. is S.0°14'W., 40.24 chs.</p> <p>From the $\frac{1}{4}$ Sec. Cor. S., continuing my measurements.</p>	
43.50	<p>Leave rolling land; descend steep S. slope. Leave fence, course W.</p>	
54.20	<p>Dry gulch, 310 ft. below top of ascent, course W.; ascend 50 ft. to</p>	
56.70	<p>Top of ridge, slopes W.; descend 200 ft. to</p>	
60.70	<p>Dry gulch, course W.; ascend 100 ft. to</p>	
64.05	<p>Top of spur, slopes W.; descend S.W. slope, 210 ft. to</p>	
79.95	<p>Fall 84 lks. E. of Cor. of Secs. 19, 24, 25, & 30, which is old post set in mound of stone, marked & witnessed as described by the Surveyor-General, except that tree in Sec. 19 is now dead and fallen. I perpetuate this Cor., as follows: At exact Cor. point Set iron post, 3 ft. long, 2 ind. diam., 24 ins. in ground for Cor. to Secs. 19, 24, 25 & 30, with brass cap, marked,</p> <p style="text-align: center;"> T2S R34E R35E S24 S19 S25 S30 1917 </p> <p>from which,</p> <p>A fir, 8 ins. diam., brs. N.28°30'E., 36 lks. dist., marked T.2 S., R.35 E., S.19, B.T. (New B.T.)</p> <p>A fir, 40 ins. diam, brs. S.79°E., 44 lks. dist., marked T.2 S., R.35 E., S.30, B.T. (Old B.T.)</p> <p>A fir, 24 ins. diam., brs. S.68°W., 108 lks. dist.,</p>	