

Allotment

Section 18

Subdivision of T. 3 North R 36 East

Subdivisional & Allotment Lines of T. 3. N. R. 36 E. Willamette, Meridan, Oregon, as surveyed by James P. Currin, U.S. Deputy Surveyor, under his Contract No. 537 dated March 5th, 1889.

Survey commenced, June 7th, 1889.

Survey completed, June 8th, 1889.

From the corner to Secs. 13, 18, 19 and 24 on W. bdy. of Township which is a post 4 ins. square firmly set in the ground marked T. 3 N, S 13 on N W. R 36 E., S 18 on N E. S 19 on S. E. R 35 E., S 24 on S. W. faces with 3 notches on N & S. edges, from which

A pine 18 ins. diam. brs. N. 8° E. 59 lks. marked T 3 N R 36 E., S 18 B T.

A pine, 36 ins. diam., bears S 65° W. 122 lks. marked R 35 E., S 24 B T., with pits 18x18x12 ins. in Secs. 13 & 19, 5 1/2 ft. dist. & mound of earth alongside.

I run

S 89° 28' E. on random line between Sec 18 & 19.

Var 18° 45' E.

Setting temporary corner at 20.00 chains. And at

39.62 Intersect the line at 1/4 Sec. corner, between Secs. 18 & 19. Which is a basalt stone, 12x16x8 ins. firmly set in the ground marked 1/4 on N. face. And mound of stone over it.

Thence I run

S 89° 28' W. on true line, between Secs 18 & 19.

Var. 18° 45' E.

20.00 Set basalt stone 12x10x7 ins. 9 ins. in the ground for 1/16 Sec. corner marked 1/16 on W. face, from which

A pine, 36 ins. diam., brs S 40° E. 43 lks. dist. marked 1/16 S. B T.

A pine, 40 ins. diam., brs S 89° E. 63 lks. dist. marked 1/16 S. B. T.