

Exterior Lines Tp. 4 S., R. 32 E.

Chains.		Feet
	W. on the N. Bdy. of Sec. 5,	
		Var. 18° 45' E.
40.00	Set basalt stone 17 x 8 x 5 in open glade on slight S.W. slope for $\frac{1}{4}$ Sec. Cor.	
	A Pine 26 in. diam brs. N. 18° W. 156 lks. dist.	
	A Pine 12 in. diam. brs. S. 37° W. 116 lks. dist.	
56.63	Intersected E. Bdy. of Tp. 3 S. R. 31 E. 13 Chs and 60 lks. N. of S.E. Cor. to Tp. 3 S. R. w1 E;	
	Set Pine post at point of intersection for Cor. to Tps. 3 & 4 S. R. 32 E. on level,	
	A Tamarack 14 in. diam. brs. N. 74° E. 32 lks. dist.	
	" " 11 " " " S. 28° E 26 " "	
	Land; surface rolling,	
	Soil; 2nd rate, mostly heavy Pine, Tamarack & Fir timber, some open glades, some dense underbrush.	
		June 14, 1881
<p>Exterior Bdy. Lines of Tp. 3 S., R. 32 E. W.M. As surveyed by George S. Pershin, U.S. Deputy Surveyor Under Contract No. 430, Dated March 23, 1882</p>		
	N. on the R. line along the E. Bdy. of Sec. 36,	
		Var.
29.50	A brook 6 lks. wide, course S.E.	
40.00	A Fir 10 in. diam. on level for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ S. on W. face from which,	
	A Fir 10 in. diam brs. E. 12 lks. dist. marked $\frac{1}{4}$ S. B.T.	
	A Fir 10 in. diam brs. S. 38° W. 14 lks dist marked $\frac{1}{4}$ S. B.T.	
79.00	Wagon road course, E & W. to Hot Sulphur Springs	
80.00	Set basalt stone 16 x 10 x 4 in. 11 ins. in ground for Cor. to Sec. 25, 36, 30 and 31 (on level) in open glad. Marked with 5 notches on N. and 1 notch on S. edges.	
	A Pine 15 ins. diam brs. N. 7° E. 234 lks dist.	