

## Subdivisional Lines of T. 3 S., R. 32 E.

Chains		Feet
	S. 89° 54' W. on a true line bet. Secs. 11 and 14, Var. 21° 15' E	
39.91	Set a basalt stone 12 x 10 x 8 ins. 8 ins. in the ground, on level, in open glade for $\frac{1}{4}$ Sec. Cor. marked $\frac{1}{4}$ on N. face. No trees near, raised a mound of stone in lieu of pits.	
79.82	The Cor. to Sec. 10, 11, 14 and 15. Land; surface undulating, Soil; 3rd and 2nd rate, some groves of Pine, Tamarack and Fir timber, but mostly open with good grass.	
	N. bet. Sec. 10 and 11. Var. 20° 30' E.	
6.25	Enter timber, course E. and W.	
29.75	A spring branch, course N.W.  Descent about 300 ft.	
40.00	Set a basalt stone 15 x 12 x 5 ins. 10 ins. in ground, on S. slope. for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face. A Pine 42 ins. diam. brs. S. 20° E. 5 lks. dist. Marked $\frac{1}{4}$ S. B.T. A Pine 18 ins. diam. brs. S. 76° W. 49 lks. dist. Marked $\frac{1}{4}$ S. B.T.	
52.00	Top of hill 200 ft. , above spring branch.	
80.00	Set a basalt stone 17 x 14 x 4 ins. 12 ins. in ground on W. slope for Cor. to Secs. 2, 3, 10 and 11. Marked with 5 notches on S. and 2 notches on E. edge from which, A Pine 12 ins. diam. brs. N. 43° E. 33 lks. dist. Marked T. 3 S., R. 32 E., S 2 B.T. A Pine 32 ins. diam. brs. S. 34° E. 16 lks. dist. Marked T. 3 S., R. 32 E., S. 11 B.T. A Pine 15 ins. diam. brs. S. 40° W. 21 lks. dist. Marked T. 3 S., R. 32 E., E. 10 B.T. A Pine 11 in. diam. brs. N. 38° W. 19 lks. dist. Marked T. 3 S., R. 32 E., S. 3 B.T.	