

## Subdivisional Lines of T 4 N., R 37 E., W.M.

Chains		Feet
	E. on a random line bet. Secs. 22 & 27	
		Var. 19° 15' E.
40.00	Set post for temp. $\frac{1}{4}$ Sec. Cor.	
80.20	Intersected N. & S. line, 38 lks. S. of Cor. to Secs. 22, 23, 26 & 27, from which Cor. I run	
	S. 89° 44' W. on a true line bet. Secs. 22 & 27	
		Var. 19° 30' E.
33.00	Cabin, about 350 lks. N. of line, spring, 200 lks. N.	
40.10	Set fir post on N.W. slope for $\frac{1}{4}$ Sec. Cor.	
	A fir, 10 ins. diam. brs. N. 50° E., 45 lks. dist.	
	A fir, 6 ins. diam. brs. S. 28° W., 35 lks. dist.	
80.20	The Cor. to Secs. 21, 22, 27 & 28	
	Land; surface, rolling	
	Soil; 2nd rate.	
	Timber, good once but nearly all cut away, fir, tamarack and pine.	
	Some farming land.	
		Aug. 20.
	N. bet. Secs. 21 & 22	
		Var. 19° 15' E.
13.00	Spring branch, course W.	
18.00	Open scattering pine timber	
40.00	Set tamarack post on S. slope for $\frac{1}{4}$ Sec. Cor.	
	A tamarack, 6 ins. diam. brs. N. 16° E., 30 lks. dist.	
	A fir, 17 ins. in diam. brs. S. 40° W. 90 lks. dist.	
63.00	Wagon road to Walla Walla, N.W. and S.E.	
66.00	Begin steep descent; thick timber	
80.00	Set basalt stone, 14 x 12 x 8 on steep N.W. hillside for	
	Cor. to Secs. 15, 16, 21 & 22.	
	A fir, 8 ins. diam. brs. N. 76° E., 67 lks. dist.	
	A fir, 12 ins. diam. brs. S. 46° E., 55 lks. dist.	
	A fir, 8 ins. diam. brs. S. 32° W., 55 lks. dist.	
	A fir, 26 ins. diam. brs. N. 75° W., 58 lks. dist.	
	Land; surface, broken	