

Subdivisional Lines of T. 4 N., R. 37 E., W.M.

Chains		Feet
	<p>9, 10, 15 and 16, which is a stone, 7 x 12 x 8 ins. above ground, marked and witnessed as described by the Surveyor General.</p> <p>Thence I run</p> <p>N. 89° 40' E. on a true line bet. Secs. 10 and 15</p> <p>Ascend W. slope of spur, through scattering timber.</p>	
3.00	<p>Top of spur, 1800 ft. above river.</p> <p>Descend steep N.E. slope of mountain into Walla Walla canyon</p>	
40.14	<p>Set a basalt stone, 15 x 10 x 8 ins., 5 ins. in ground, struck rock, raised mound of stone around for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on the N face; raised mound of stone, 2 ft. base, 1$\frac{1}{2}$ ft. high N. of Cor. Pits impracticable.</p>	
51.35	<p>Creek, 3 lks. wide, in ravine 200 ft. deep, course N. 15° E.</p> <p>Ascend over spur.</p>	
59.75	<p>Top of spur, 200 ft. high, brs. N. and S.</p> <p>Descend along steep N. slope into Walla Walla Canyon.</p>	
71.00	<p>Foot of mountain, 2000 ft. below Sec. Cor.</p>	
71.00	<p>Over stony bottom, not subject to inundation.</p>	
73.50	<p>Left bank of the Walla Walla River, 50 lks. wide, 3 ft. deep, swift current, stony bottom, course N. 60° W.</p> <p>Over sandy bottom land, not subject to inundation.</p>	
77.10	<p>Pack trail, brs. E. and N. 60° W.</p>	
77.50	<p>Ascend along steep S. slope of mountain</p>	
80.28	<p>The Cor. of Secs. 10 and 15</p> <p>Land; mountainous</p> <p>Soil; sandy loam and stony, 1st and 4th rate.</p> <p>Timber; scattering tamarack, fir, pine and alder, cotton-wood.</p> <p>Mountainous land; 80.24 Chs.</p> <p style="text-align: right;">June 16, 1902</p>	
40.00	<p>Thence I run</p> <p>N. 0° 02' W. on a random line bet. Secs. 10 & 11</p> <p>Set temp. $\frac{1}{4}$ Sec. Cor.</p>	