

## Resurvey of Exterior Bdy. of T 4 N., R. 38 E., W.M. (N. Bdy.)

Chains		Feet
6.00	Enter heavy timber	
7.00	A stump desert, brs. N. and S.	
20.40	Spring branch, 6 lks. wide, runs. S.	
20.90	Perpendicular bluff, 75 ft. high, brs. N. and S.	
33.00	Spring branch, 6 lks. wide, runs, S. 30° W.; ascend.	
36.90	The old standard $\frac{1}{4}$ Sec. Cor., a fir, 12 ins. diam., marked and witnessed as described by the surveyor general, brs. S. 16 lks. dist. I destroyed all traces of this old standard $\frac{1}{4}$ Sec. Difference in measurement of 40.00 Chs. by two sets of chainmen is 10 lks., position of middle point: By 1st set, 39.95 Chs. By 2nd set, 40.05 Chs., the mean of which	
40.00	Falls on a point of rock, 20 x 15 x 12 ins. above basaltic ledge, from which I, cut cross (x) at the exact Cor. point for standard $\frac{1}{4}$ Sec. Cor., marked S. C. $\frac{1}{4}$ on N. face, from which: A fir, 10 ins. diam. brs. N. 18 $\frac{1}{2}$ ° E., 1 ch. 16 lks. dist., marked $\frac{1}{4}$ S., 35 B.T. A fir, 10 ins. diam. brs. N. 86° W., 74 lks. dist. marked $\frac{1}{4}$ S. 34, B.T.	
52.00	Top of spur, brs. N. 40° E., and S. 40° W. Descent through scattering timber, hill brs. N. 60° E., and S. 60° W.	
58.00	Bottom of ravine, course S. Ascend	
62.00	Top of spur, descend steep slope	
73.00	Spring branch, 2 lks. wide, runs, S.E.	
74.00	Spring branch, 2 lks. wide, runs, S. Ascend.	
74.90	The old standard Cor. of Secs. 34 & 35; set basalt stone in mound of stone, marked and witnessed as described by the surveyor general, brs. S. 13 lks. dist. I destroy all trace of the old Cor.	
	A point, 800 ft. below the last Sec. Cor. and the difference in measurement of 80.00 Chs. by two sets of chainmen is 8 lks.; position of middle point: By 1st set, 79.96 Chs. By 2nd set, 80.04 Chs.; the mean of which is	
80.00	Set a basalt stone, 20 x 16 x 10 ins. 15 ins. in the ground,	