

Subdivisional Lines of T 4 N R 38 E., W.M.

Chains		Feet
79.00	<p>Begin descent</p> <p>The Cor. of Secs. 7, 8, 17 & 18</p> <p>Land; mountainous</p> <p>Soil; ligh, 3rd rate.</p> <p>Timber; fir, pine and spruce</p> <p>Undergrowth, laurel and willow</p> <p>Mountainous or heavily timbered land or land covered with dense undergrowth and exceptionally difficult to survey,</p> <p>79.00 Chs.</p>	
38.00	<p>From the Cor. of Secs. 9, 10, 15 & 16 on the Sectional Correction line I run</p> <p>S. 0° 2' E. bet. Secs. 15 & 16</p> <p>Ascend E. slope through scattering timber and dense undergrowth.</p> <p>Top of divide, 300 ft. high, brs. S.E. and N.W.</p> <p>Thence descend over precipitous S.W. slope</p>	
40.00	<p>Set a basalt stone, 15 x 10 x 5 ins., 10 ins. in the ground for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face; from which</p> <p>A pine, 24 ins. diam. brs. S. 41° 30' E., 84 lks. dist., marked $\frac{1}{4}$ S 15 B T</p> <p>And raised a mound of stone, 2 ft. base and 1 ft. and a half high W. of Cor.</p> <p>No other br. trees available.</p>	
80.14	<p>Intersect the E. and W. line, 192 lks. E. of the Cor. of Secs. 21 & 22, heretofore described.</p> <p>At the point of intersection I set a basalt stone, 15 x 10 x 5 ins., 10 ins. in the ground for closing Cor. to Secs. 15 & 16, marked C C on N. and with 3 grooves on E. and 3 grooves on S. edges and raised a mound of stone, 2 ft. base and 1 ft. and a half high W. of Cor.</p> <p>I destroy all markings on the old Cor. referring to Secs. 16 & 15</p> <p>Land; mountainous</p> <p>Soil; 1st and 2nd rates</p> <p>Timber; fir, pine, spruce</p>	