

First Standard Parallel through 39 E., W M.

Chains

A fir, 10 ins. diam., brs. N.59°E., 18 lks. dist.,
marked S C T 5 N R 39 E S 32 B T.

A fir, 25 ins. diam., brs. N.38°W., 24 lks. dist.,
marked S C T 5 N R 39 E S 31 B T.

A fir, 6 ins. diam., brs. S.12°E., 30 lks. dist.,
marked S C T 4 N R 39 E S 6 B T.

Land; rugged, broken & mountainous.

Soil; 4th rate & stony.

Thick fir, tamatack and pine.

Dense undergrowth of fir, tamatack, pine, hackleberry &
maple.

Dependent Resurvey, S. Bdy., T 5 N R 39 E W M.,
As surveyed by Otis O. Gould, U.S. Surveyor,
Under Special Instructions, Group 135,
Dated April 11, 1929.

"Reestablishment of survey executed by Rufus S. Moore, U.S.
Deputy Surveyor, in 1882."
N.89°47'W. on true line on S. Bdy. of Sec. 31.

Desc. 130 ft. over NW. slope, through heavy timber and
dense undergrowth.

5.70 Ravine, course N.; asc. 31 ft. over NE. slope.

8.10 The original standard Cor. of Secs. 31 & 32, determined by
reference to the record bearings and distances to the
original bearing trees.

I now change this Cor. to an angle point.

At point for Cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground, for angle point, with brass cap marked

A P
T5N R39E
S 31

1932

from which

A fir snag, 10 ins. diam., brs. N.59°E., 18 lks. dist.,
marked S C T 5 N R 39 E S 32 B T. (Old B.T.)

A fir stump, 6 ins. diam., brs. S.12°E., 30 lks. dist.,
no marks. (Old B.T.)

A fallen fir snag, 25 ins. diam., brs. N.38°W., 24 lks.
dist., marked S C T 5 N R 39 E S 31 B T. (Old B.T.)

A fir, 8 ins. diam., brs. N.33°E., 38 lks. dist.,
marked A.P S 31 B T. (New B.T.)

A fir, 12 ins. diam., brs. N.61°W., 56 lks. dist., marked
A P S 31 R T (New B.T.)