

Dependent Resurvey First Standard Parallel thru 39E.,W.M.

Chains

Obliterate the marks on old original bearing trees.

Thence

S.89°28'W., continuing measurements.

8.70 Spur, slopes NW.; desc. 750 ft. over W. slope, changing to NW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in ground to solid rock and in mound of stone to top, for standard $\frac{1}{4}$ Sec. Cor., with brass cap, marked

S C
 $\frac{1}{4}$ S 31

1932

from which

A fir, 6 ins. diam., brs. N.51°E., 44 lks. dist., marked $\frac{1}{4}$ S 31 S C B T.

A fir, 20 ins. diam., brs. N.16°W., 33 lks. dist., marked $\frac{1}{4}$ S 31 S C B T.

Continue to desc. 161 ft. over N.W. slope.

48.36 The original standard $\frac{1}{4}$ Sec. Cor. of Sec. 31, which is a basalt stone, 20 x 10 x 6 ins., firmly set, marked S C $\frac{1}{4}$ on N. face.

I now change this Cor. to an angle point.

At point for Cor.

Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to solid rock and in a mound of stone to top, for angle point, with brass cap marked

A P
T5N R39E
S 31

1932

from which

A yellow pine stamp, 44 ins. diam., brs. N.20°E., 10 lks. dist., marked S C $\frac{1}{4}$ S B T. (Old B.T.)

A yellow pine snag, 20 ins. diam., brs. S.70°E., 162 lks. dist., marked S C $\frac{1}{4}$ S B T. (Old B.T.)

A pine, 8 ins. diam., brs. N.32°E., 71 lks. dist., marked A P S 31 B T. (New B.T.)

A pine, 22 ins. diam., brs. N.52°W., 71 lks. dist., marked A P S 31 B T. (New B.T.)

Obliterate the marks on the old Cor. stone and on the old bearing trees.

Thence

N.89°50'W., continuing measurements.

Continue to desc. 264 ft. over S.W. slope.

61.60 Spur, slopes S.W., continue to desc. 354 ft. over NW.slope.

72.70 Ravine, course NW.; asc. 36 ft. over NE. slope.