

## Exterior Lines of T. 4 S., R. 31 E., W.M.

Chains		Feet
	Soil; 2nd and 3rd rate, mostly heavy timber Pine, Tamarack and Fir. Good grass in openings. Some good farming land.	
	N. on the W. Bdy. of Sec. 7, Var. 21° 00' E.	
22.00	Leave heavy timber, course E. and W.	
40.00	Set basalt stone 14 x 12 x 12 on S. slope in mound of stone for $\frac{1}{4}$ Sec. Cor.	
79.00	Enter timber, course E. and W.	
80.00	Set basalt stone 16 x 10 x 8 ins. on N.W. slope for Cor. to Secs. 6, 7, 1 and 12.	
	A Pine 12 ins. diam. brs. N. 34° E. 30 lks. dist.	
	A Pine 8 ins. diam. brs. S. 45° E. 27 lks. dist.	
	A Pine 16 ins. diam. brs. S. 54° W. 34 lks. dist.	
	A Pine 13 ins. diam. brs. N. 35° W. 45 lks. dist.	
	Land; surface rolling Soil; 2nd and 1st and 3rd rates; some timber Pine, Tamarack and Fir; good grass; some good farming land.	
	N. on the W. Bdy. of Sec. 6, Var. 21° 45' E.	
40.00	Set basalt stone 18 x 8 x 7 on steep N. slope for $\frac{1}{4}$ sec. Cor.	
	A Tamarack 12 ins. diam. brs. E. 12 lks. dist.	
	A Tamarack 10 ins. diam. brs. N. 80° W. 10 lks. dist.	
50.00	A ravine opens, W.	
54.00	Leave timber, course E. and W.	
65.74	To a point on the S. Bdy. of T. 3 S., R. 30 E., 790 lks. W. of the Cor., Tps. 3 S., Rs. 30 and 30 $\frac{1}{2}$ E. Set basalt stone 18 x 8 x 8 ins. and post in mound of stone at this point for Cor. to Tps. 4 S., Rs. 30 and 31 E. No trees.	
	Land; surface very broken, Soil; 2nd and 3rd rate; heavy timber, Pine, Tamarack and Fir. Some underbrush. Oct. 18, 1880	
	Exterior Lines of T. 4 S., R. <del>30</del> <sup>27</sup> E., W.M. As surveyed by Edward W. Saunderson, U.S. Deputy Surveyor Under Contract No. 417 Dated August 24, 1881.	
	I begin at the post, the Cor. to Tps. 4 and 5 S., R. 29 & 30 E., which is a post 4 ins. sq. marked, T. 4 S., R. 30 E., S. 31 on N.E. face,	