

Exterior Lines of T. 4 S., R. 29 E. W.M.

Chains		Feet
	<p>Pine, Tamarack and Fir timber, about 3/4 of this mile, remainder open or scattering. Some undergrowth of Pine, Fir and Tamarack.</p>	
	<p>N. bet. Secs. 1 and 6, Var. 20° 15' E.</p>	
34.00	Springs and spring branch, course W.	
40.00	<p>Set a basalt stone 18 x 12 x 8 ins. 12 ins. in ground for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face, from which, A Pine 14 ins. diam. brs. N. 42° E. 50 lks. dist. marked $\frac{1}{4}$ S.B.T. A Pine 14 ins. diam. brs. N. 56° W. 34 lks. dist., marked $\frac{1}{4}$ S.B.T.</p>	
44.50	Wagon road course, E. and W. to timber,	
45.00	<p>A spring branch course W. at 68.00 chs. I make careful and diligent search, but cannot find any trace of Cor. to T 3 S., R. 29 and 30 E. I now proceed to the Cor. of Secs. 29, 30, 31 and 32 in T. 3 S., R. 30 E. and run and measure W. 80.00 chs. and can find no trace of Cor. to Secs. 30 and 31 on W. Bdy., Thence I run and measure S. 40.00 chs. and find the $\frac{1}{4}$ Sec. Cor. which is a stone 20 x 12 x 10 ins. on slight N.W. slope and from this point I establish the old Cor. of T. 3 S., R. 29 and 30 E., by running S. 40.00 chs. Set a basalt stone 20 x 8 x 8 ins. in a mound of stone on rocky S.W. hillside for Cor. to T. 3 S., R. 29 and 30 E., marked with 6 notches on N.E.S. and W. edges, this being an old Cor. I marked it as near the old style as possible.</p>	
67.26	<p>Set a basalt stone 16 x 10 x 7 ins. 11 ins. in ground and post 3 ft. long 5 ins. diam. with S.E. and S.W. sides, faces N.E. and N.W., blank stone marked with S.E.W. edges 6 notches on each post marked, T. 4 S., R. 30 E., S. 6 on S.E. T. 4 S., R. 29 E. S. 1 on S.W.</p>	