

Exteriors of Township 4 S., Range 33 E., W. M.  
 As surveyed by George S. Pershin, U.S. Deputy Surveyor,  
 Under Contract No. 410,  
 Dated July 28, 1881.

## Chains

From the Cor. to Tps. 4 & 5 S., Rs. 32 & 33 E., which is a  
 post, 4 ins. sq., marked

T 4 S R 33 E S 31 on N.E.

T 5 S R 3 3 E S 6 on S.E.

T 5 S R 3 2 E S 1 on S.W.

T 4 S R 3 2 E S 3 6 on N.W.

and with 6 notches on each edge, and mound of stone  
 around post, I run

S.89°51'E. on true line bet. Secs. 31 & 6.

Var. 20°00'E.

19.00 Enter timber.

39.68 Set basalt stone, 15 x 12 x 5 ins., 10 ins. in ground, for  
 $\frac{1}{4}$  Sec. Cor., marked  $\frac{1}{4}$  on N. face.

A pine, 18 ins. diam., brs. N.32°W., 39 lks. dist.,  
 marked  $\frac{1}{4}$  S., B.T.

79.68 Set basalt stone, 16 x 12 x 5 ins., 11 ins. in ground, for  
 Cor. to Secs. 5, 6, 31 & 32, marked with 1 notch on W.  
 and 5 notches on E. edges, from which,

A pine, 6 ins. diam., brs. N.7°E., 109 lks. dist.,  
 marked T 4 S R 3 3 E S 3 2 B T.

A pine, 5 ins. diam., brs. S.14°E., 68 lks. dist.,  
 marked T 5 S R 3 3 E S 5 B T.

A pine, 10 ins. diam., brs. S.50°W., 52 lks. dist.,  
 marked T 5 S R 3 3 E S 6 B T.

No tree N.W.

Raised mound of stone alongside in lieu of pits.

Land; surface undulating.

Soil; 2nd & 3rd rate.

Pine & tamarack timber on E. 60 chs.

S.89°51'E. on true line bet. Secs. 32 & 5.

Var. 20°15'E.

Ascending.

32.00 On ridge and begin descent, top 100 ft. above Cor., ridge  
 N. & S.

40.00 Set basalt stone, 12 x 8 x 7 ins., 8 ins. in ground, for  $\frac{1}{4}$