

W. Bdy., T.4 S.,R.33 $\frac{1}{2}$ E.,W. M.

Chains	
	<p>20 x 10 x 5 ins., marked with 5 notches on S. and 1 notch on N. edges, from which</p> <p>A pine, 18 ins. diam., brs. N.26°E., 78 lks. dist., marked T.4 S.,R.34 E.,S.6,B.T.</p> <p>A fir, 10 ins. diam., brs. S.62°E., 110 lks. dist., marked T.4 S.,R.34 E.,S.7,B.T.</p> <p>A fir, 28 ins. diam., brs. S.40°W., 23 lks. dist., marked T.4 S.,R.33 E.,S.12,B.T.</p> <p>A fir, 10 ins. diam., brs. N.72°W., 117 lks. dist., marked T.4 S.,R.33 E.,S.1,B.T.</p> <p>Destroyed marks referring to Secs. 6 & 7.</p>
25.00	Top of hill, brs E. & W., 250 ft. above Cor. to Secs. 6 & 7.
36.50	Descend hill brs. N.E. & S.W.
54.26	The $\frac{1}{4}$ Sec. Cor.
<p>Subdivisional Lines, T. 4 S.,R.33 E.,W. M. As surveyed by Geo. S. Pershin,U.S.Deputy Surveyor, Under Contract No. 410, Dated July 28, 1881.</p>	
N. bet. Secs. 35 & 36.	
Var.18°15'E.	
Ascending through timber.	
40.00	<p>Set basalt stone, 18 x 10 x 6 ins., 12 ins. in ground, on N.W. slope for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face.</p> <p>A pine, 28 ins. diam., brs. E., 34 lks. dist., marked $\frac{1}{4}$ S.,B.T.</p> <p>A pine, 40 ins. diam., brs. N.40°W., 15 lks. dist., marked $\frac{1}{4}$ S.,B.T.</p>
49.50	A spring branch, course S.E.
80.00	<p>Set basalt stone, 20 x 8 x 6 ins., 15 ins. in ground, for Cor. to Secs. 25, 26, 35 & 36, marked with one notch on S. and E. edges, from which</p> <p>A pine, 22 ins. diam., brs. S.34°W., 127 lks. dist., marked T.4 S.,R.33 E.,S.35,B.T.</p> <p>A pine, 14 ins. diam., brs. N.72°W., 120 lks. dist., marked T.4 S.,R.33 E.,S.26,B.T.</p> <p>No other trees; a glade on E. side. Raised mound of stone</p>