Subdivisional Lines, T.4 S.,R.33 E.,W. M.

Chains	
40.00	Set basalt stone, 16 x 12 x 4 ins., 11 ins. in ground,for ¼ Sec. Cor., marked ¼ on W. side (ascent 200 ft.),from which
	A pine, 18 ins. diam.,brs. S.45°E., 11 lks. dist., marked ¼ S.,B.T.
	A pine, 4 ins. diam.,brs. S.16°W., 12 lks. dist., marked ¼ S.,B.T.
80.00	Set basalt stone, 12 x 8 x 6 ins., 8 ins. in ground,for Cor. to Secs. 17, 18, 19 & 20, marked with 3 notches on S. and 5 notches on E. edges,from which
	A pine, 40 ins. diam.,brs. N.35°E., 149 lks. dist., marked T.4 S.,R.33 E.,S.17,B.T.
	A pine, 36 ins. diam.,brs. S.53°E., 95 lks. dist., marked T.4 S.,R.33 E.,S.20,B.T.
	A pine, 20 ins. diam.,brs. S.18°W., 90 lks. dist., marked T.4 S.,R.33 E.,S.19,B.T.
	No tree on N.W., open glade.
	Raised mound of stone alongside instead of pits.
	Land; surface very broken and steep on S. ½ mile,N.½ mile undulating.
	Soil; 3rd rate.
	Timber; pine, tamarack & fir, with glades.
	Sept. 24, 1881.
	E. on random line bet. Secs. 17 & 20.
	Var.20°00'E.
32.50	Stream, 6 lks. wide, course S. Descent 150 ft.
40.00	Set temp. ¼ Sec. Cor.
80.47	Intersected N. & S. line, 18 lks. N. of Cor. to Secs. 16, 17, 20 & 21, (ascent 200 ft.)
	Thence I run
	N.89°52'W. on true line bet. Secs. 17 & 20.
	Var.21°00'E.
40.23	Set basalt stone, 12 x 10 x 7 ins., 8 ins. in ground,for ¼ Sec. Cor., marked ¼ on N. side,from which
	A pine, 38 ins. diam.,brs. N.54°W., 15 lks. dist.