

Subdivisional Lines, T.4 S., R.33 $\frac{1}{2}$ E., W. M.
As surveyed by same U.S. Deputy Surveyor
Under same Contract & date.

Chains	<p>I commenced at the Cor. to Secs. 1, 2, 35 & 36, on S. Bdy. of the Tp., which is a basalt stone, 24 x 15 x 15 ins., 18 ins. in ground, marked with 1 notch on E. and 2 notches on W. edges, with pits, 18 x 18 x 12 ins. in each Sec., 5$\frac{1}{2}$ ft. dist., and mound of earth, 2 ft. high and 4$\frac{1}{2}$ ft. base alongside.</p> <p>I run N. bet. Secs. 35 & 36. Var. 19°40'E.</p> <p>Through timber.</p> <p>10.00 Enter heavy pine timber and descending to 37.00 Camas Creek, 10 lks. wide, runs W. 40.00 To the margin of a swampy bottom, course E. & W. Set basalt stone, 15 x 12 x 8 ins., 10 ins. in ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{2}$ on W. face, from which, A pine, 4 ins. diam., brs. S.70°W., 30 lks. dist., marked $\frac{1}{4}$ S., B.T. A pine, 10 ins. diam., brs. N.65°E., 96 lks. dist., marked $\frac{1}{4}$ S., B.T.</p> <p>80.00 Set basalt stone, 13 x 8 x 7 ins., 9 ins. in ground, for Cor. to Secs. 25, 26, 35 & 36, marked with 1 notch on E. and 1 notch on S. edges, from which, A pine, 5 ins. diam., brs. S.35°W., 15 lks. dist., marked T.4 S., R.33$\frac{1}{2}$ E., S.35, B.T. A pine, 4 ins. diam., brs. S.47°E., 10 lks. dist., marked T.4 S., R.33$\frac{1}{2}$ E., S.36, B.T. A pine, 4 ins. diam., brs. N.54°E., 20 lks. dist., marked T.4 S., R.33$\frac{1}{2}$ E., S.25, B.T. A pine, 4 ins. diam., brs. N.72°W., 10 lks. dist., marked T.4 S., R.33$\frac{1}{2}$ E., S.26, B.T.</p> <p>Land; rolling. Soil; 2nd rate. Heavily timbered with pine, fir and tamarack, N.70 chs. Dense undergrowth of young pine & fir.</p>
--------	---