

Exterior Line, T.5 S., R.34 E. W. M.

Chains	<p>Land; rolling.</p> <p>Soil; on upland 2nd & 3rd rate.</p> <p>Soil; on bottom 1st rate.</p> <p>Scattering pine timber.</p>
	<p>Subdivisional Lines, T.4 S., R.34 E., W. M. As surveyed by Rufus S. Moore, Under Contract No. 451, dated June 12, 1882.</p>
	<p>From the Cor. to Secs. 33 & 34 on the S. Bdy. of Tp. which is a post, 5 ins. sq., 24 ins. in ground, marked T.4 S., R.34 E., S.34, on N.E. T.4 S., R.34 S., S.33 on N.W. T.5 S., R.34 E., S.4 on S.W. and T.5 S., R.34 E., S.3 on S.E. faces, with 3 notches on E. & W. edges, from which A pine, 16 ins. diam., brs. N.8°E., 62 lks. dist., marked T.4 S., R.34 E., S.34, B.T. A pine, 7 ins. diam., brs. N. 18°W., 97 lks. dist., marked T.4 S., R.34 E., S.33, B.T. A tamarack, 40 ins. diam., brs. S.66°W., 54 lks. dist., marked T.5 S., R.34 E., S.4, B.T. A pine, 12 ins. diam., brs. S.23°E., 70 lks. dist., marked T.5 S., R.34 E., S.3, B.T.</p> <p>I run N. bet. Secs. 33 & 34. Var. 20°30'E.</p>
1.25	Dry gulch, course N.W.
40.00	<p>Set basalt stone, 17 x 9 x 6 ins., 12 ins. in ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face, from which A pine, 8 ins. diam., brs. N.75°W., 79 lks. dist., marked $\frac{1}{4}$ S., B.T. A pine, 45 ins. diam., brs. N.85°E., 86 lks. dist., marked $\frac{1}{4}$ S., B.T.</p>
68.50	Spring branch, 2 lks. wide, runs N.W.
80.00	<p>Set basalt stone, 12 x 8 x 6 ins., 8 ins. in ground, for Cor. to Secs. 27, 28, 33 & 34, marked with 1 notch on S. and 3 notches on E. edges, from which</p>