

Subdivisional Lines, T 5 N R 38 E W M.,  
 As surveyed by Geo. R. & Wm. E. Campbell, U.S. Deputy Surveyors,  
 Under their joint Contract No. 699 & Special Instructions,  
 Dated March 23, 1899.

## Chains

Having determined a true meridian at the Cor. of Secs. 35  
 and 36, reestablished by me, July 19, 1899;

A basalt stone, 18 x 12 x 5 ins., above ground, marked &  
 witnessed as described in the field notes of resurvey  
 returned to the Surveyor-General.

Thence I run

N.0°1' W. bet. Secs. 35 & 36.

Ascending steep, rocky hillside, through scattering timber;  
 hill brs. N.W. & S.E.

6.00 Ravine, course W.

10.50 Top of rise or point; brs. S.60°W.; descend.

15.50 Ravine, 150 ft. deep, course S.70°W.; ascend.

24.00 Top of rise on ridge-point; brs. S.70°W.; descend. steep  
 northward slope through heavy timber.

39.50 Ravine, course N.50°W.; ascend; hill brs. N.30°W & S.80°E.

40.00 A point, 350 ft. above Sec. Cor. &

Set fir post, 3 ft. long, 3 ins. sq., 24 ins. in ground,  
 for  $\frac{1}{4}$  Sec. Cor., marked  $\frac{1}{4}$  S on W. face; from which

A tamarack, 15 ins. diam., brs. N.80°E., 14 lks. dist.,  
 marked  $\frac{1}{4}$  S 36 B T.

A tamarack, 15 ins. diam., brs. N.40°W., 15 lks. dist.,  
 marked  $\frac{1}{4}$  S 35 B T.

51.45 Stream, 5 lks. wide, runs S.70°W.; ascend steep S. slope.

57.00 Ridge, brs. N.30°E & S.30°W.

75.00 Descend N. slope.

80.00 A point, 850 ft. above Sec. Cor. S. and

Set fir post, 3 ft. long, 3 ins. sq., 24 ins. in ground,  
 for Cor. to Secs. 25, 26, 35 & 36, marked

T 5 N S 25 on N.E.

R 38 E S 36 on S.E.

S 35 on S.W. nad

S 26 on N.W. faces, with

1 notch on S. & E. edges;

from which

A spruce, 24 ins. diam., brs. N.32°E., 41 lks. dist.,