

Subdivisional Lines, T 5 N R 38 E W M.

Chains	N.0°3' W. bet. Secs. 3 & 4. Ascending steep hill through heavy timber, brs. N.10°E. and S.10°W.
2.25	Top of high spur, brs. N.55°W. and S.55°E. Descend steep hill, brs. N.30°W. and S.30°E.
7.75	Rill, 1 lk. wide, runs E. ascend steep hill, brs. N.40°E. and S.40°W.
10.00	Enter glade, brs. E. & W.
11.50	Enter timber, brs. E. & W.
14.95	A fir, 28 ins. diam., on line, I mark with 2 notches on N. and S. sides.
24.00	More gradual ascent.
32.40	A tamarack, 28 ins. diam., on line, I mark with 2 notches on N. & S. sides.
33.00	Trail, from settlements westward to the Grand Ronde, brs. N.40°E. and S.40°W.
40.00	On summit of divide bet. headwaters of Mill Creek and Walla Walla River, 750 ft. above Sec. Cor., brs. N.80°E. & S. 80°W. Set a yew post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ S on W. face; from which A fir, 28 ins. diam., brs. N.40°E., 28 lks. dist., marked $\frac{1}{4}$ S 3 B T. A fir, 20 ins. diam., brs. N.59°W., 44 lks. dist., marked $\frac{1}{4}$ S 4 B T. Thence descend gradually; hill brs. E. & W.
47.00	Steeper descent.
52.55	A fir, 26 ins. diam., on line, I mark with 2 notches on N. and S. sides. Thence down ravine.
77.00	Branch, 6 lks. wide, runs N.E. Thence along E. slope.
87.50	Rill, 1 lk. wide, runs N.E.
92.45	A point, 1400 ft. below $\frac{1}{4}$ Sec. Cor. and Intersect N. Bdy. of Tp., finding no trace of old Cor., de-