

Subdivisional Lines, T 5 N R 38 E W M.

Chains	
	Thence I run N.89°47'W. on true line bet. Secs. 16 & 21. Descending through scattering timber. Hill brs. N.10°W. and S.10°E.
5.00	Enter heavy timber, brs. N. & S.
9.00	Rill, 1 lk. wide, runs N.20°W. Thence along N. slope.
15.00	Descend. Hill brs. N. & S.
25.72	Foot. Stream, 3 lks. wide, runs N.30°W. Ascend. Hill brs. N.60°W. & S.60°E.
36.00	Top of spur, brs. N.40°E. and S.70°W.
40.00	A point, 100 ft. below Sec. Cor. and Set basalt stone, 15 x 12 x 8 ins., 10 ins. in ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face; from which A fir, 12 ins. diam., brs. S.85°E., 12 lks. dist., marked $\frac{1}{4}$ S 21 B T. A fir, 24 ins. diam., brs. N.80°W., 16 lks. dist., marked $\frac{1}{4}$ S 16 B T. Thence down steep descent brs. N.50°E. & S.50°W.
45.50	Foot of hill.
45.95	N. Fork of Walla Walla River, 30 lks. wide, flows S.60°W. Thence over bottom land, southward slope.
47.50	Trail, brs. N.50°E. and S.50°W. Thence along southward slope.
60.75	Ravine, course S.E.
67.50	Leave timber, brs. N.30°W. and S.30°E. Thence steeper ascent, with same bearing.
73.75	Top of spur, brs. N.20°W. and S.20°E. Descend.
78.50	Enter timber, brs. N. & S.
80.00	A point, 500 ft. above $\frac{1}{4}$ Sec. Cor. and the Cor. of Secs. 16, 17, 20 & 21.