

## Subdivision of T 5 N., R. 39 E.

Chains		Feet
21.00	South Fork of the Walla Walla River Trail, brs. NE. and SW.	
25.00	Leave South Fork of the Walla Walla River, 35 lks. wide, course S.; from NW.; continue along gradual broken W. slope.	
25.43	South Fork of the Walla Walla River Trail, brs. NW. and SE.	
32.00	Creek, 5 lks. wide, course W.; asc. 153 ft. over SW. slope.	
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked	
	$\begin{array}{c} \frac{1}{4} \\ \uparrow \\ \text{S19}   \text{S20} \\ \downarrow \\ 1932 \end{array}$	
	from which	
	A fir, 11 ins. diam., bears S. $46^{\circ}$ E., 10 lks. dist. marked $\frac{1}{4}$ S 20 B T.	
	A spruce, 10 ins. diam., bears N. $68^{\circ}$ W., 4 lks. dist., marked $\frac{1}{4}$ S 19 B T.	
	Continue to asc. 65 ft. over SW. slope	
42.85	Spur, slopes SW.; desc. 37 ft. over NW. slope.	
46.05	Ravine, course SW.; asc. 547 ft. over SE. slope.	
62.00	Spur, slopes SW., from N.; asc. 436 ft. over S. slope, on spur.	
75.50	Leave spur, slopes S., from NE.; desc. 99 ft. over NW. slope.	
79.50	Bottom of descent, bears E. and W.; continue along W. slope.	
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to solid rock and in a mound of stone to top, for cor. of secs. 17, 18, 19, and 20, with brass cap marked	
	$\begin{array}{c} \text{T5N R39E} \\ \text{S18}   \text{S17} \\ \text{S19}   \text{S20} \\ 1932 \end{array}$	
	from which	
	A fir, 12 ins. diam., bears N. $20^{\circ}$ E., 88 lks. dist., marked T 5 N R 39 E S 17 B T.	
	A fir, 28 ins. diam., bears S. $17^{\circ}$ E., 34 lks. dist., marked T 5 N R 39 E S 20 B T.	
	A fir, 26 ins. diam., bears S. $50^{\circ}$ W., 38 lks. dist., marked T 5 N R 39 E S 19 B T.	
	A fir, 22 ins. diam., bears N $65^{\circ}$ W., 52 lks. dist., marked T 5 N R 39 E S 18 B T.	
	Land, mountainous.	