

## Exterior Lines of T. 5 S., R. 29 E., W.M.

Chains		Feet
40.00	<p>Set a basalt stone, 15 x 10 x 5 ins., 110 ins. in ground, on slight N. slope for <math>\frac{1}{4}</math> Sec. Cor., marked <math>\frac{1}{4}</math> on W. face, from which,</p> <p>A Pine, 6 ins. diam. brs. S. 53° E., 28 lks. dist. marked <math>\frac{1}{4}</math> S.B.T.</p> <p>A Pine, 24 ins. diam. brs. S. 28° W., 62 lks. dist. marked <math>\frac{1}{4}</math> S.B.T.</p>	
30.00	<p>Set a pine post, 4<math>\frac{1}{2}</math> ft. long, 4 ins. sq. 2 ft. in the ground on slight N.E. slope for Cor. to secs. 4 &amp; 5 S., Rs. 29 and 30 E., marked,</p> <p>T. 4 S., R. 30 E., S. 31 on N.E.</p> <p>T. 5 S., R. 30 E., S. 6 on S.E.</p> <p>T. 5 S., R. 29 E., S. 1 on S.W.</p> <p>T. 4 S., R. 29 E., S., 36 on N.W., from which,</p> <p>A Pine, 9 ins. diam. brs. N. 62° E., 19 lks. dist. marked T. 4 S., R. 30 E., S. 31 B.T.</p> <p>A Pine, 9 ins. diam. brs. S. 34° E., 21 lks. dist. marked T. 5 S., R. 30 E., S. 6 B.T.</p> <p>A Pine, 9 ins. diam. brs. S. 34° E., 21 lks. dist. marked T. 5 S., R. 30 E., S. 6 B.T.</p> <p>A Pine, 9 ins. diam. brs. S. 68° W., 32 lks. dist. marked T. 4 S., R. 29 E., S. 36 B.T.</p>	
	Land; surface rolling,	
	Soil; 3rd and 2nd rate. Some open Pine, Tamarack and Fir timber with large open glades.	
	June 7, 1882	
	<p>Resurvey of a Portion of the Exterior of T. 5 S., R. 29 E. As surveyed by Frank W. Campbell, U.S. Deputy Surveyor, Under Contract No. 468. Dated April 12, 1883.</p>	
	<p>Survey commenced April 28, 1883, with a Butes improved Solar Compass. In subdividing this Tp. I commenced by running N. on the E. Bdy. of Sec. 36, Var. 19° E.</p> <p>and at,</p>	
14.60	I found the $\frac{1}{4}$ Sec. Cor., and at	
1.24	The Cor. to Secs. 25, 30, 31 & 36, thence, N. on the E. Bdy of Sec. 25.	