Subdivisional Lines of T. 5 S., R. 30 E. W.M.

Chains		Feet
40.00	Set temp. ¼ Sec. Cor.	
72.00	Enter timber, course N. and S.	
79.87	Intersect E. Bdy. of Tp. 20 lks. S. of Cor. to Secs. 24, 25, 19 and 30, which is a basalt stone 17 x 10 x 7 ins. firmly set in ground, marked with 4 notches on N. and 2 notches on S. edges, from which	
	A Fir 10 ins. diam. brs. N. 47° E. 31 lks. dist. marked T. 5 S., R. 31 E., S. 19B.T.	
	A Fir 12 ins. diam. brs. S. 42° E. 38 lks. dist. marked T. 5 S., R. 31 E., S. 30 B.T.	
	A Fir 8 ins. diam. brs. S. 40° W. 23 lks. dist. marked T. 5 S., R. 30 E., S. 25 B.T.	
	A Pine 20 ins.diam. brs. N. 13° W. 88 lks. dist. marked T. 5 S., R. 30 E., S. 24 B.T.	
	Thence I run,	
	S. 89° 51' W. on true line bet. Secs. 24 and 25 with same Var.	
39.93	Set basalt stone 18 x 13 x 8 ins. 12 ins. in ground for ¼ Sec. Cor., marked ¼ on N. face and raised a mound of stone alongside.	
79.87	The Cor. to Secs. 23, 24, 25 and 26.	
	Land; rolling,	
	Soil; 3rd rate. Heavily timbered with Pine, 17.87 Chs.	
	N. bet. Secs. 23 and 24.	
	Var. 20° E.	
10.00	Enter heavy Pine timber, course E. and W.	
39.75	Brook, 6 lks wide, course E.	
40.00	Set basalt stone 18 x 11 x 9 ins. 12 ins. in ground for ¼ Sec. Cor., marked ¼ on W. face, from which,	
	A Pine 18 ins. diam. brs. N. 72° W. 54 lks. dist. marked ¼ S.B.T.	
	A Pine 30 ins. diam.brs. N. 79° E. 4 lks. dist. marked ¼ S.B.T.	
76.90	Brook, 5 lks. wide, course N.E.	
80.00	Set basalt stone 12 x 10 x 10 in 8 ins. in ground for Cor.	