

S. Bdy. of T. 5 S., R. 32 E., W.M.
 As surveyed by, George S. Pershin, U.S. Deputy Surveyor,
 Under Contract No. 362,
 Dated Aug. 2, 1880.

Chains		Feet
	From Cor. to Tps. 5 S., Rs. 31 & 32 E., I run, E. on a true line along the S. Bdy. of Sec. 31 Var. 17° 45' E.	
40.00	Set basalt stone, 14 x 10 x 5, on level for $\frac{1}{4}$ Sec. Cor. A Pine, 44 ins. diam. brs. N. 37° E., 117 lks. dist. A Pine, 28 ins. diam. brs. S. 38° W., 54 lks. dist.	
75.00	Enter timber and begin to descend	
80.00	Set basalt stone, 18 x 10 x 4 ins., on E. face of bluff for Cor. to Secs. 31 & 32. A Fir, 17 ins. diam. brs. N. 63° W., 52 lks. dist. A Fir, 8 ins. diam. brs. N. 12° E., 11 lks. dist. Land; surface undulating, Soil; 2nd rate, scattering timber, occasionally E. 5 Chs. heavy timber, Pine, Tamarack and Fir. Good grass. Large part good farming land.	
	E. on a true line along the S. Bdy. of Sec. 32 Var. 20° 45' E.	
3.25	Spring branch, course N.	
15.00	Leave heavy timber, course N. and S.	
35.00	Enter timber, course N. and S.	
40.00	Set basalt stone, 18 x 12 x 10, on S.W. slope for $\frac{1}{4}$ Sec. Cor. A Pine, 16 ins. diam. brs. N. 75 lks. dist. A Pine, 22 ins. diam. brs. S. 44° E., 19 lks. dist.	
80.00	Set basalt stone, 17 x 10 x 4 on slight S.W. slope for Cor. to Secs. 32 & 33. A Pine, 40 ins. diam. brs. N. 54° E., 268 lks. dist. No other trees. Land; surface rolling, Soil; 2nd and 3rd rate; timber heavy in places, but mostly scattering Pine, Tamarack and Fir. Good grass. Some good farming land.	