

## Subdivisional Lines of T. 5 S., R. 32 E., W.M.

Chains		Feet
	Var. 20° 15' E.	
28.00	Begin steep descent of creek bluff Timber course S.E. and N.W.	
33.00	Cable creek, 30 lks. wide, course N.W.	
40.04	Set basalt stone, 16 x 10 x 4, near top of bluff, for $\frac{1}{4}$ Sec. Cor. A Pine, 36 ins. diam. brs. N. 10° W., 59 lks. dist. A " 10 " " " S. 28° E., 49 " "	
51.00	Leave timber, course S.E. and N.W.	
80.08	The Cor. to Sec. 23, 24, 25 & 26 Land; surface undulating, except creek canyon Soil; 2nd and 3rd rate, heavy Tamarack, Pine and Fir timber along creek. Good grass on prairie.	
N. bet. Sec. 23 & 24		
	Var. 21° 30' E.	
37.00	Enter timber, course S.E. and N.W.	
40.00	Set basalt stone, 18 x 16 x 7, on steep N.E. face of bluff for $\frac{1}{4}$ Sec. Cor. A Tamarack, 16 ins. diam. brs. S. 48° E., 37 lks. dist. A " 8 " " " S. 78° W., 71 " "	
49.50	Cable creek, course N.W.	
58.00	On bluff and leave timber, course N.W. and S.E.	
80.00	Set basalt stone, 18 x 10 x 6, & post in mound of stone on slight N.W. slope for Cor. to Secs. 13, 14, 23 & 24. Land; surface undulating except creek canyon. Soil; 2nd and 3rd rate. Good Tamarack, Pine, Fir timber along creek, good grass on prairie.	
E. on a random line bet. Secs. 13, & 24.		
	Var. 22° 45' E.	
40.00	Set post for temp. $\frac{1}{4}$ Sec. Cor.	
40.50	Intersected E. Bdy., 36 lks. S. of Cor. to Sec. 13 & 24, from which Cor. I run S. 89° 45' W. on a true line bet. Secs. 13 & 24. Var. 19° 30' E.	