

Subdivisional Lines of T. 5 S., R. 32 E., W.M.

Chains		Feet
	A Pine, 10 ins. diam. brs. N. 32° E., 36 lks. dist.	
	A Tamarack, 16 ins. diam. brs. S. 24° E., 100 lks. dist.	
48.00	Camas creek, 100 lks. wide, course S. 75° W.	
56.00	Leave timber, course S.W. and N.E.	
79.96	The Cor. to Sec. 4, 5, 8 & 9.	
	Land; surface mostly broken	
	Soil; 3rd and 2nd rate, heavy Pine, Tamarack and Fir timber with open glades.	
<hr/>		
	N. on a random line bet. Sec. 4 & 5	
		Var. 19° 15' E.
40.00	Set post for temp. $\frac{1}{4}$ Sec. Cor.	
80.13	Intersected N. Bdy., 36 lks. W. of Cor. to Sec. 4 & 5, from which Cor. I run,	
	S. 00° 15' W. on a true line bet. Sec. 4 & 5	
		Var. 19° 30' E.
26.50	Leave timber, course E. and W.	
40.13	Set basalt stone, 14 x 12 x 10 on level for $\frac{1}{2}$ Sec. Cor.	
80.13	The Cor. to Secs. 4, 5, 8 & 9.	
	Land; surface undulating	
	Soil; 2nd and 3rd rate. Pine timber on N. 26 Chs., remainder good grass. Some good farming land.	
		June 8, 1881
<hr/>		
	N. bet. Sec. 31 & 32	
		Var. 20° 45' E.
	A Fir, 6 ins. diam. brs. N. 14° E., 11 lks. dist.	
	A Fir, 16 ins. diam. brs. N. 62° W., 51 lks. dist.	
8.75	Brook, 8 lks. wide, course N.W.	
40.00	Set basalt stone, 17 x 8 x 5 on S. slope of bluff for $\frac{1}{4}$ Sec. Cor.	
	A Pine, 20 ins. diam. brs. S. 68° E., 53 lks. dist.	
	A Pine, 22 ins. diam. brs. S. 52° W., 42 lks. dist.	
80.00	Set basalt stone, 20 x 10 x 8 in open glade in mound of stone for Cor. to Sec. 29, 30, 31 & 32.	