

Subdivisional Lines, T.5 S., R.33 E., W. M.

Chains

A pine, 12 ins. diam., brs. N.28°E., 62 lks. dist.,
marked T.5 S., R.33 E., S.12, B.T.

A pine, 12 ins. diam., brs. S.47°E., 137 lks. dist.,
marked T.5 S., R.33 E., S.13, B.T.

A pine, 10 ins. diam., brs. S.67°W., 122 lks. dist.,
marked T.5 S., R.33 E., S.14, B.T.

A pine, 14 ins. diam., brs. N.70°W., 141 lks. dist.,
marked T.5 S., R.33 E., S.11, B.T.

Land; surface broken.

Soil; 3rd & 2nd rate.

Heavily timbered with pine, fir & tamarack timber, with underbrush same. Some open glades.

E. on random line bet. Secs. 12 & 13.

Var. 19°30'E.

Irregular broken surface.

40.00 Set temp. $\frac{1}{4}$ Sec. Cor.

44.00 Spring branch, course N.E.

71.50 " " " N.

80.12 Intersected E. Bdy., 43 lks. N. of Cor. to Secs. 12 & 13,
which is a stone, projecting 6 ins. above ground, 2
notches on N. and 4 notches on S. edges.

A pine, 15 ins. diam., brs. N.28°E., 21 lks. dist.,
marked T.5 S., R.34 E., S.7, B.T.

A pine, 16 ins. diam., brs. S.38°E., 55 lks. dist.,
marked T.5 S., R.34 E., S.18, B.T.

A pine, 18 ins. diam., brs. S.40°W., 93 lks. dist.,
marked T.5 S., R.33 E., S.13, B.T.

A pine, 24 ins. diam., brs. N.66°W., 46 lks. dist.,
marked T.5 S., R.33 E., S.12, B.T.

From which Cor., I run

N.89°42'W. on true line bet. Secs. 12 & 13.

Var. 20°00'E.

40.06 Set basalt stone, 18 x 10 x 5 ins., 12 ins. in ground, on
E. slope, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face.

A fir, 14 ins. diam., brs. N.16 lks. dist., marked $\frac{1}{4}$
S., B.T.