

Subdivisional Lines, T.5 S.,R.33 E.,W. M.

Chains	marked $\frac{1}{4}$ S.,B.T.
80.00	Descent 150 ft. Set basalt stone, 16 x 8 x 6 ins., 11 ins. in ground, on slight N.W. slope, for Cor. to Secs. 4, 5, 8 & 9, marked with 5 notches on S. and 4 notches on E. edges. A tamarack, 8 ins. diam.,brs. N.43°E., 20 lks. dist., marked T.5 S.,R.33 E.,S.4,B.T. A tamarack, 8 ins. diam.,brs. S.15°E., 60 lks. dist., marked T.5 S.,R.33 E.,S.9,B.T. A tamarack, 10 ins. diam.,brs. S.30°W., 28 lks. dist., marked T.5 S.,R.33 E.,S.8,B.T. A fir, 6 ins. diam.,brs. N:40°W., 49 lks. dist.,marked T.5 S.,R.33 E.,S.5,B.T. Land; surface undulating. Soil; 3rd & 2nd rate. Mostly open scattering pine, tamarack & fir timber, with open glades.
	E. on random line bet. Secs. 4 & 9. Var.20°E. Surface rolling.
40.00	Set temp. $\frac{1}{4}$ Sec. Cor.
45.00	Top of main ridge, course N. & S. Ascent 100 ft.
77.25	Spring branch, course N. Descent 100 ft.
80.08	Intersected N. & S. line, 18 lks. N. of Cor. to Secs. 3, 4, 9 & 10, from which Cor., I run N.89°52'W. on true line bet. Secs. 4 & 9. Var.20°15'E.
40.04	Set basalt stone, 17 x 10 x 7 ins., 12 ins. in ground, on slight W. slope, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face. A pine, 10 ins. diam.,brs. N.61°E., 43 lks. dist., marked $\frac{1}{4}$ S.,B.T. A pine, 10 ins. diam.,brs. S.52°W., 105 lks. dist., marked $\frac{1}{4}$ S.,B.T.
80.08	The Cor. to Secs. 4, 5, 8 & 9. Land; surface rolling.