

Exterior lines of T. 7 S., R. 31 E.

Chains	Feet
34.00	Old mining ditch, course N. 85° E.
40.00	Set fir post for $\frac{1}{4}$ Sec. Cor.; from which A Fir, 7 ins. diam. brs. N. 8° W., 23 lks. dist. A Fir, 7 ins. diam. brs. S. 32° W., 42 lks. dist.
80.00	To Cor. to T. 6 & 7 S., Rgs: 31 & 32 E. Land; E. $\frac{3}{4}$ hilly; W. $\frac{1}{4}$ Rolling Scattering pine and fir timber.
June 3, 1881	
Exterior Bdy. of T. 6 S., R. 31 E., W.M. As surveyed by Rufus S. Moore, U.S. Deputy Surveyor Under Contract No. 382. Dated March 23, 1881	
N. on E. Bdy. of Sec. 36	
Var. 13° 15' E.	
25.60	Foot of hill, brs. E. and W.
26.77	N. fork of John Days river, 180 lks. wide, runs S. 70° W. Set flag at this point and cross to opposite bank where flag brs. Due S. I then run a base W. 180 lks. when flag brs S. 45° E.
29.00	Ascend hill, brs. E, and W.
40.00	Set a basalt stone, 16 x 10 x 5, in a mound of stone for $\frac{1}{4}$ Sec. Cor.
70.00	Top of hill, brs. E. and W.
80.00	Set a baslat stone, 16 x 12 x 10, in a mound of stone for Cor to Secs. 25, 30, 31 & 36.
Land; hilly and broken	
Soil; 3rd rate.	
Scattering pine on S. 25 Chs.; Alder on river.	
N. on E. Bdy. of Sec. 25	
Var. 19° 30' E.	
40.00	Set a basalt stone, 20 x 16 x 10, in a mound of stone for $\frac{1}{4}$ Sec. Cor.
80.00	Set a basalt stone, 18 x 10 x 6, in a mound of stone for Cor. to Secs. 19, 24, 25 & 30. Land; rolling prairie